

Power supply



- MeanWell ELG/HLG-series
- Constant Voltage 24VDC
- Not dimmable
- IP67



Output: Constant Voltage(CV)
Input voltage: 100 - 240VAC
Output voltage: 24VDC
Connection type: 30 cm H05RN-F 2x1mm² in
 AWG18 out
IP-grade: IP67
Operating temperature: -40°C ~ +85°C

Art.no.	Product	Brand	Output power	Dimensions:
S32010	Power supply 24V	ELG	75W	L:180 W:63 H:35,5 mm
S32011	Power supply 24V	ELG	100W	L:199 W:63 H:35,5 mm
S32012	Power supply 24V	ELG	150W	L:219 W:63 H:35,5 mm
S32013	Power supply 24V	ELG	240W	L:244 W:71 H:35,5 mm
S32019	Power supply 24V	HLG	320W	L:252 W:90 H:43,8 mm
S32020	Power supply 24V	HLG	600W	L:280 W:144 H:38,5 mm
S32076	Power supply 24V	VS	200W	L:206 W:68,6 H:37 mm

Power supply



- Compact LED driver
- Constant Voltage (CV)
- Electronic short circuit protection: reversible
- Protection against "no load"
- SELV (Safety Extra Low Voltage)
- IP20



Output: Constant Voltage(CV)
Input voltage: 100 - 240VAC
Output voltage: 24VDC
Connection type: Srew Connection
IP-grade: IP20
Operating temperature: -15°C ~ +45°C

Art.no.	Product	IP-grade	Output power	Dimensions:
S32071	Power supply 24V CV EDXe	IP20	30W	L:153 W:41,4 H:32 mm
S32072	Power supply 24V CV EDXe	IP20	60W	L:180 W:52 H:30 mm
S32073	Power supply 24V CV EDXe	IP20	75W	L:180 W:52 H:30 mm
S32074	Power supply 24V CV EDXe	IP20	120W	L:300 W:40 H:30 mm