

OTP25T3M



General Information

Extended Product Type:	OTP25T3M
Product ID:	1SCA022401R0090
EAN:	6417019130859
Catalog Description:	OTP25T3M Safety switch
Long Description:	Safety switch 3-p.400V AC23A 15kW AC22A 32A Plastic enclosure IP65 Black Selector handle

Categories

Products » Low Voltage Products and Systems » Enclosed Switches » Enclosed Safety Switches

Ordering

EAN:	6417019130859
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85365080

Dimensions

Product Net Width:	145 mm
Product Net Height:	200 mm
Product Net Depth:	90 mm
Product Net Weight:	0.9 kg

Container Information

Package Level 1 Units:	1 piece
Package Level 1 Width:	152 mm
Package Level 1 Height:	138 mm
Package Level 1 Length:	203 mm
Package Level 1 Gross Weight:	1 kg
Package Level 1 EAN:	6417019130859

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4
--------------	---

Additional Information

Cable Entry Position:	Top and bottom
Cable Outlets Per Side:	2xM32+M16
Conventional Thermal Current (I_{the}):	Fully Enclosed 50 A
Degree of Protection:	acc. to IEC 60529 IP65
Enclosure Material:	Plastic
IIT Publishing Status:	Level 0 - Information enabled
Number of Auxiliary Contacts NO:	1
Number of Poles:	3
Pollution Degree:	3
Position of Line Terminals:	Top in - bottom out
Position of Neutral Terminals:	Top in - bottom out
Position of PE Terminals:	Top in - bottom out
Product Main Type:	OT25
Product Name:	Safety switch

Rated Operational Current AC-22A (I_e):	(500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A (I_e):	(380 ... 415 V) 30 A (500 V) 30 A (690 V) 20 A
Rated Operational Power AC-23A (P_e):	(220 ... 240V) 7,5 kW (400V) 15 kW (500V) 15 kW (690V) 15 kW
Rated Operational Voltage:	750 V

Certificates and Declarations (Document Number)

Declaration of Conformity - CE:	1SCC340003D0203
RoHS Information:	1SCC340034D0201

Classifications

E-nummer:	3140152
ETIM 5.0:	EC000249 - Protection switch disconnecter housing
Object Classification Code:	Q

