



SEARCH

Product features TKS - KLIKSEAL® TKS - KLIKSEAL® RAL 7035

KLIKSEAL® - Animation

Product data TKS - KLIKSEAL®

Product data TKS - KLIKSEAL® for thin materials

Installation TKS - KLIKSEAL®



Material
Protection class
Temperature range
Test standard
Semko report
Tariff No.
UNSPSC Code
Halogen-Free

TPE and Polyamide 66 UL listed material
IP67 / IP65
-20°C...+125°C (1)
EN60529:1991 + A1,
EN50262:1998 + A1 + A2
1111146 + 606620
39269097
39121431

(1) Unstressed material.

* Cable Anchorage Type A, according to EN 50262.
** 8,1 - 8,9 mm only approved for tension relief.
*** Varies depending on the thickness of material installed in.

Measurements & Variants

Information

Downloads



Lightgrey RAL 7035

E-number	Size	IP67 and Cable Anchorage Type A* for Cable Ø		A mm	B for IP67/65		H	H2 mm	D1 mm	D*** mm	Pcs/pack
		mm	mm		mm	mm					
1475803	M20	7 - 11	4 - 11	20.5	2 - 5		17 - 20	5.7	4	29,3 - 34,5	50
1475804	M25	7 - 13**	4 - 13	25.5	2 - 5		17 - 20	5.7	5	34,3 - 40,0	50

Tapper Sealing Technology AB
Lerbacksgatan 2
SE-571 38 Nässjö
Sweden

Telephone: +46 380 558180
Fax: +46 380 12303

