

MODUS PL 7000, wide body 1575mm, LED 840 , body PE, opal PMMA cover, IP65, driver 1200mA

Code: PL7000L2WPM4ND

EAN: 8596099022600



Mechanical properties

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes	Material housing:	Plastic
Suitable for wall mounting:	Yes	Rated ambient temperature (°C):	-10...+45

Light source

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	7700
System power (W):	53	Luminaire efficacy (lm/W):	145
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White	Energy efficiency class of the built-in lamp:	A++, A+, A (LED)

Optical system

Optical system:	PM	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Dimensions

Length (mm):	1575	Width (mm):	135
Height/depth (mm):	100	Built-in length (mm):	1100
Size version:	L	Weight (kg):	2,8

Electical properties

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		