

PRODUCT-DETAILS

ADU 300

ADU 300 Uninsulated connector



General Information

Extended Product Type	ADU 300
Product ID	2CGD000502A1000
EAN	7331980000586
Catalog Description	ADU 300 Uninsulated connector
Long Description	Uninsulated connector suitable for connection to ABB Kabeldon IP 00 PE/PEN busbars. Connectable conductor area 50-300 mm ² .

Popular Downloads

Data Sheet, Technical Information	2CGC0036
Instructions and Manuals	2CGD000666S1000

Dimensions

Product Net Width	30 mm
Product Net Height	64 mm
Product Net Depth / Length	73 mm
Product Net Weight	0.166 kg

Technical

Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Operational Voltage	690 V
Standards	IEC 61238-1-1
Cable Cross-Section	50...300 mm ²
Degree of Protection	acc. to IEC 60529 IP00
Tightening Torque	20 N·m Wire-Clamp 20...35 N·m

Certificates and Declarations (Document Number)

Declaration	2CGC0049
Instructions and Manuals	2CGD000666S1000
RoHS Information	2CGC0040

Container Information

Package Level 1 Units	bag 1 piece
Package Level 1 Width	30 mm
Package Level 1 Depth / Length	73 mm
Package Level 1 Height	64 mm
Package Level 1 Gross Weight	0.166 kg
Package Level 2 Units	box 50 piece
Package Level 2 Width	524 mm
Package Level 2 Depth / Length	194 mm
Package Level 2 Height	215 mm
Package Level 2 Gross Weight	8.3 kg

Classifications

ETIM 6	EC000001 - Busbar terminal
ETIM 7	EC000001 - Busbar terminal
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Sweden)	0732796

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Kabeldon IP-System

