

# ECA 100 ipro KH



## Short description

Two-step small room fan with electric internal shutter and fully automatic humidity system, DN 100

## Application examples

Bathroom, Shower, Sauna vestibule, Utility room


Article number 0084.0208

## Technical data

Model	Humidity control
Air flow volume	78 m <sup>3</sup> /h / 92 m <sup>3</sup> /h
Speed controllable	–
Reversing capacity	–
Type of voltage	Alternating current
Rated voltage	230 V
Frequency	50 Hz
Nominal output	10 W / 13 W
I <sub>max</sub>	0,08 A
Degree of protection	IP X5
Mains cable	3 / 1,5 mm <sup>2</sup>
Installation site	Ceiling / Wall
Type of installation	Surface-mounted
Installation position	any
Material	Synthetic material
Colour	Traffic white, similar to RAL 9016
Weight	0,7 kg
Shutter	integrated
Type of shutter	electrical
Nominal size	100 mm
Airstream temperature at I <sub>Max</sub>	40 °C
Overrun time	8 min / 17 min / 25 min
Start delay	0 s / 50 s / 90 s / 120 s
Sound pressure level	27 dB(A) / 32 dB(A) (Distance 3 m, Free-field conditions)
Range	A
EAN	4012799842088


# ECA 100 ipro KH

## Characteristic curve



- ① Performance level 1
- ② Performance level 2

## Dimensioned drawing [mm]



- ① Cable entry