

S7S 1600 PR211-LI-In=1600A 3p F EF



General Information

Extended Product Type:	S7S 1600 PR211-LI-In=1600A 3p F EF
Product ID:	1SDA012657R1
EAN:	8015644126575
Catalog Description:	S7S 1600 PR211-LI-In=1600A 3p F EF
Long Description:	CIRCUIT-BREAKER ISOMAX S7S 1600 THREE-POLE FIXED WITH EXTENDED FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR 211 LI R 1600

Categories

Products » Low Voltage Products and Systems » Circuit Breakers » Moulded Case Circuit Breakers » Isomax

Ordering

EAN:	8015644126575
Minimum Order Quantity:	1 piece
Customs Tariff Number:	85362090

Container Information

Package Level 1 Units:	1 piece
Package Level 1 EAN:	8015644126575

Environmental

RoHS Status:	Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q3
---------------------	---

Additional Information

Electrical Durability:	5000
IIT Publishing Status:	Level 0 - Information enabled
Number of Poles:	3
Product Main Type:	SACE Isomax
Product Name:	S7 - Automatic CB - Fixed
Rated Current (I_n):	1600 A
Rated Impulse Withstand Voltage (U_{imp}):	8 kV
Rated Operational Voltage:	690 V AC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(500V AC) 35 kA (230V AC) 85 kA (220V AC) 85 kA (380V AC) 50 kA (690V AC) 20 kA (440V AC) 40 kA
Rated Uninterrupted Current (I_u):	1600 A
Release Type:	PR211/P-LI
Standards:	IEC-947-2(D)
Sub-type:	S7
Suitable For:	S7
Suitable for Product Class:	Moulded Case Circuit Breakers
Terminal Connection Type:	Front Extended
Test Voltage at Industrial Frequency for 1 Minute:	3000 V
Version:	Fixed

Certificates and Declarations (Document Number)

Declaration of Conformity - CE: 1SDL000160R0057**RoHS Information:** 1SDL000193R0001

Classifications

ETIM 4.0: EC000228 - Power circuit-breaker for trafo/generator/installation prot.**ETIM 5.0:** EC000228 - Power circuit-breaker for trafo/generator/installation prot.**Object Classification Code:** Q

