

## Ferrule - A 6 -12 - 3200328

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ferrule, Length: 12 mm, Color: silver

The figure shows variant A 1-6

### Why buy this product

- ✓ The A 0,25.. ferrules can also be used to process 0.14 mm<sup>2</sup> conductors
- ✓ The dimensions of the ferrules conform to DIN 46228-1
- ✓ The ferrules without plastic sleeve are made from soft tin-plated electrolytic copper

### Key commercial data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 500 pc                                                                                                  |
| Minimum order quantity               | 500 pc                                                                                                  |
| GTIN                                 | <br>4 017918 093976 |
| Weight per Piece (excluding packing) | 0.23 g                                                                                                  |
| Custom tariff number                 | 85369010                                                                                                |
| Country of origin                    | Germany                                                                                                 |

### Technical data

#### Dimensions

|                                              |        |
|----------------------------------------------|--------|
| Length (b)                                   | 12 mm  |
| Maximum stripping length                     | 12 mm  |
| Inner dimension of the insulating collar (d) | 4.7 mm |
| Ferrule diameter                             | 3.5 mm |
| Sleeve wall thickness                        | 0.2 mm |

#### Ambient conditions

|                            |        |
|----------------------------|--------|
| Max. permanent temperature | 105 °C |
|----------------------------|--------|

#### General

|          |        |
|----------|--------|
| Color    | silver |
| Material | E-CU   |

## Ferrule - A 6 -12 - 3200328

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27060701 |
| eCl@ss 4.1 | 27060701 |
| eCl@ss 5.0 | 27400201 |
| eCl@ss 5.1 | 27400201 |
| eCl@ss 6.0 | 27400201 |
| eCl@ss 7.0 | 27400201 |
| eCl@ss 8.0 | 27400201 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000005 |
| ETIM 3.0 | EC000005 |
| ETIM 4.0 | EC000005 |
| ETIM 5.0 | EC000005 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30212109 |
| UNSPSC 7.0901 | 27121703 |
| UNSPSC 11     | 27121703 |
| UNSPSC 12.01  | 27121703 |
| UNSPSC 13.2   | 27121703 |

### Approvals

#### Approvals

##### Approvals

CSA / CSAus / EAC / cCSAus

##### Ex Approvals

##### Approvals submitted

#### Approval details

|                                                                                         |
|-----------------------------------------------------------------------------------------|
| CSA  |
|-----------------------------------------------------------------------------------------|

|       |
|-------|
| CSAus |
|-------|

## Ferrule - A 6 -12 - 3200328

### Approvals

|     |
|-----|
| EAC |
|-----|

|        |
|--------|
| cCSAus |
|--------|

---

Phoenix Contact 2015 © - all rights reserved  
<http://www.phoenixcontact.com>