



Description

Article

Part No.: 32 168

EQUES[®] 60Classic

adapter 250 A

terminals 95 mm² at top

110 x 320

System

60Classic

Product group 05

Untergruppe 36

pack size 1

EAN 4021267321680

Advantages of the product

Movable fastening rails with M4 slide nuts for safe mounting of the switching devices.

catalog page 2015 : 2/17

Classification

eCl@ss 6.1 27370304

eCl@ss 7.1 27370304

ETIM 4.0 EC001531

ETIM 5.0 EC001531

Approvals

Standards

IEC 61439-1:2011

Approvals

CSA, UL, Germanischer Lloyd



Type number: 60250

UL file: E123577, UL category (for USA): NMTR2 <http://www.ul.com>

UL file: E123577, UL category (for Canada): NMTR8 <http://www.ul.com>

CSA file: 110285, CSA class: 3211-37 <http://directories.csa-international.org>

CCC approval: no certification required

Product data

Electrical data

Rated current (IEC): 250 A

Rated voltage (IEC) AC: 690 V

Rated current (UL): 250 A

Rated voltage (UL) AC: 600 V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 22.1 W.

(The power dissipation for operation with rated current would be 34.6 W.)

rated isolation voltage U_i (AC): 800 V

Rated surge voltage U_{imp} : 6 kV

max. permitted voltage (IEC) AC: 800 V

max. permitted voltage (IEC) DC: 800 V

rated peak withstand current I_{pk} : 55.8 kA

Mechanical data

W x H x D: 110 x 320 x 101

Weight: 160.4 kg/100


Poles: 3-pole

Material properties

Body:

temperature stability 125°C,
self-extinguishing in acc. to UL 94,
creepage resistance CTI 200,
halogen-free

Accessories



32 937

slide nut M5

for 32 168, 32 214, 32 215, 32 216
