



464220EX

TAIS-EX INTERLOCKED SOCKET SOCKET WITH MCB 2P+E 16A 220V 6H FOR ATEX ZONE 2D 3G

Registry		Technical data	
Net weight	3,495	Dimensions	125X380X160 mm
Min order quantity	1	Hole type	M25
EAN Code	8014950033287	Frequency	50-60Hz
Reference Standards EN 60079-0/A11: 2013 EN 60079-0: 2012 EN 60079-15: 2010 EN 60079-31: 2014 EN 60309-1/A1: 2007 EN 60309-1/A1EC: 2014 EN 60309-1/A2: 2012 EN 60309-1: 1999 EN 60309-2/A1: 2007 EN 60309-2/A2: 2012 EN 60309-2: 1999 EN 60309-4/A1: 2012 EN 60309-4: 2007		Protection level	IP66
		Poles	2P+ $\frac{1}{2}$
		Clock Position	6
		Nominal Operating Voltage	230V
		Manufacturing Material	Thermosetting
		Width	125 mm
		Nominal current	16A
		Execution	WALL MOUNTING
		Protection	MCB
		Insulation Class	II
		Atex	
		ATEX application zone	Zona/Zone 2, 21 and 22
		Notified body (CE)	 0051
		Certificate Number IECEx	IECEx EXA 15.0004X
		Atex Dust Nominal Current	16
		Atex Gas Nominal Current	16
		Atex Dust Marking	Ex tb IIIC T80°C Db
		Atex Gas Marking	Ex nR IIC T6 Gc
		Certificate Number ATEX	TÜV IT 13 ATEX 049 X
		GAS Dissipable Power	-
		DUST Dissipable Power	-
		Min. Amb. Temp.	-20°C
		Max. Amb. Temp.	+40°C
		Group & Cat. ATEX GAS	II 3G
		Group & Cat. ATEX DUST	II 2D
Marks		Attachments	
		DXF drawing	