

## ErgoQIC 08

### Atlas Copco standard profile

The ErgoQIC 08 is a full flow quick coupling with no air restriction inside the coupling. It is suitable for assembly tools, drills and small grinders. Upgrading any air system with ErgoQIC 08 will give the benefits of productivity and energy efficiency.


- Full flow coupling.
- Ergonomic design, small size and low weight.
- Strong and durable.
- Safety feature according to EN 983 / ISO 4414.











## Technical Data

Max flow capacity 64 cfm (7 psi ΔP)  
 Economical air flow 38 cfm (3 psi ΔP)  
 Max working pressure 230 psi  
 Temperature range 14°F to +158°F

Flow chart. ErgoQIC 08 M15U and ErgoNIP 08 M10U



### ErgoQIC 08 and ErgoNIP 08, 38 cfm (recommended air flow at 90 psi pressure)

Connection type	Coupling ErgoQIC 08	Ordering No.	Size		Connection type	Nipple ErgoNIP 08	Ordering No.	Size	
			mm	in				mm	in
<b>H – Hose</b> 	H06 H08 H10	8202 1110 04 8202 1110 12 8202 1110 38	6.3 8 10	1/4 5/16 3/8	<b>H – Hose</b> 	H06 H08 H10	8202 1210 37 8202 1210 45 8202 1210 52	6.3 8 10	1/4 5/16 3/8
					<b>SH – Safety Hose<sup>a</sup></b> 	SH06 SH08 SH10	8202 1210 39 8202 1210 47 8202 1210 50	6.3 8 10	1/4 5/16 3/8
<b>M – Male</b> 	M08U M10U M15U	8202 1115 09 8202 1115 17 8202 1115 25	1/4" NPT 3/8" NPT 1/2" NPT		<b>M – Male</b> 	M06U M08U M10U	8202 1215 08 8202 1215 16 8202 1215 24	1/8" NPT 1/4" NPT 3/8" NPT	
<b>F – Female</b> 	F08U F10U	8202 1115 30 8202 1115 35	1/4" NPT 3/8" NPT		<b>F – Female</b> 	F08U F10U	8202 1215 32 8202 1215 35	1/4" NPT 3/8" NPT	
Protective cover 									

<sup>a</sup> For joining hoses longer than 3 meters.