

THREADED, BLANK FLANGE



Design features

- Made of ductile iron, epoxy powder coated
- Flange sized according to EN 1092-2 and drilled in accordance with EN 1092-2 | PN 10 standard; PN 16 for DN 200 to DN 300 please specify on order - other standards on request


DN	MOP (PN)	Thread No. 8100				Thread No. 8100L								
		1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
40														
50														
60														
65														
80														
100	10													
125														
150														
200														
250														
300														

Threaded flange

No. 8100

No. 8100L

with internal thread ISO 228



DN	MOP (PN)	C	Weight No. 8100						
			1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
40					1,80	1,70			
50			2,30	2,20	2,20	2,10			
60					3,00				
65			3,20	3,10	3,00	3,00	2,70		
80		19	3,60	3,50	3,40	3,40	3,40	2,90	
100	10		4,30	4,20	4,20	4,20	3,90	3,70	3,30
125			5,40	5,50	5,50	5,30	5,20	5,10	4,70
150			7,00	6,90	6,90	6,80	6,70	6,60	6,20
200		20	11,50	11,30	11,30	11,00	10,60	10,30	
250		22			16,20	16,00	15,00		
300		25				23,10			

DN	MOP (PN)	C	Weight No. 8100L						
			1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
50				2,70	2,60	2,60	2,50		
60			3,40	3,20	3,00	2,80	2,60		
65			3,40	3,20	3,00	2,80	2,60		
80	10	32	4,00	3,90	3,90	3,90	3,80	3,40	
100			5,90	5,70	5,70	5,50	5,20	4,80	4,50
125			8,20	8,10	8,10	7,90	7,50	7,00	6,60
150			9,50	9,30	9,20	9,10	8,70	8,50	8,10
200			15,50	15,40	15,30	15,10	14,80	14,50	14,20

Design features

- Made of ductile iron, epoxy powder coated
- Flange sized according to EN 1092-2, and drilled in accordance with EN 1092-2, | PN 10 standard; PN 16 for DN 200 to DN 400 please specify on order - other standards on request
- Other nominal diameters on request

DN	MOP (PN)	C	Weight
40			2,00
50			2,90
60			2,80
65			3,80
80			4,00
100			4,60
125			5,70
150			7,60
200		20	11,40
250		22	17,20
300		25	25,50
400			38,00

Blank flange

No. 8000

