

DN	No. 2170E2	No. 4000STE2
50		
65		
80		
100		
125		
150		
200		
250		
300		
350		
400		



## Position indicator

### No. 2170E2

- For visual display of the wedge position in **E2** valve
- Limit switch (No. 2190) for electrical signal transmission set-up is possible
- Actuation by handwheel (No. 7800)
- DN 50 to 200 for retrofitting on standard **E2** upper section

## Limit switch

### No. 2190

- For set-up on the 2170**E2** position indicator
- Body made of metal
- Operating current 230 V / 3 A
- IP 66 / IP 67 protection type
- Switching principle: slow-action contact element
- Design of the switching function: positively driven contact
- Number of openers: 1
- Number of closers: 1

## E2 valve "short"

### No. 4000STE2

- **E2** valve with flange with installed position indicator

Order No.	DN	Weight	
7850	¾"-2"	0,08	
	50-200	0,30	



## Anti-operation cap

### No. 7850

- Only suitable for extension spindles for service valves and **E2** valve
- Use: protection against misuse (e.g.: mains disconnection valve)

Order No.	DN	Weight	
7851	¾"-2"	0,20	
	50-200	1,00	



## T-key adapter

### No. 7851

- Suitable for anti-operation cap No. 7850