

ENSTO

Branching connector

KE10.1



Code KE10.1
 GTIN 6418677400049
 Name Branching connector
 Al 4x10-35 mm² / Cu 1.5-25 mm²
 Description KE10.1 connector can be used for aluminium and copper conductors. Tightening torque is 10 Nm. The connectors are used either inside metal poles or in separate boxes.

Vendor

Technical specification

Certificates

Standards: IEC 61238-1

Dimensions

Net Weight: 0.044 kg
 Conductor size Al: 10 ... 35 mm²
 Conductor size Cu: 1.5 ... 25 mm²
 Conductor diameter: 1.7 ... 9 mm

Electrical values

Highest system voltage: 1 kV

Mechanical

Tightening torque: 10 Nm

Others

ETIM Class: EC000306

ETIM 7 Technical specification

etim

Model: Branch

Colour insulation:	Transparent
Material insulation:	PC
Grease filling against corrosion:	True
Nominal cross section:	1.5 ... 35 mm ²
Core diameter:	1.7 ... 9 mm
Max. number of cores:	1
Interrupt free shifting:	True

Packaging

Pallet package

Unit:	pcs
Package size:	5250
Depth:	1200 mm
Width:	800 mm
Height:	890 mm

Default package

Unit:	pcs
Package size:	50
Depth:	218 mm
Width:	218 mm
Height:	126 mm
Weight:	2.332 kg
Volume:	5.988024 l