

EnoX luminaire and loudspeaker housing



LUFTDICHT

- for installing luminaires, loudspeakers, displays and much more
- Minimum distance inside: min. 40 mm all round
- integrated stress relief (retention force) in accordance with DIN VDE 0606 / DIN EN 60670-1
- only for insulation material with heat resistance > 250°C
- use only tested heat-resistant cables (N2 GMH 2G) and temperature-resistant terminals (e.g. T100)
- for installation devices up to LxW 120 x 220 mm or Ø 120 mm
- Heat distortion resistant to 220°C
- with 4 screws (FX4)

- **Length:** 368 mm
- **Width:** 268 mm
- **Depth:** 60 mm
- **Length on the inside:** 300 mm
- **Width on the inside:** 200 mm
- **Depth on the inside:** 57 mm
- **Conduit entries for DIN EN conduits up to Ø 25 mm:** 4
- **Cable entries 3 x 1.5 mm²:** 4
- **Cable entries 3 x 2.5 mm² or 5 x 1.5 mm²:** 4

Art. No.: 9350-21

- **Inner packaging:** ST
- **Outer packaging:** 10 ST
- **Individual net weight:** 367,000 G
- **Single volume:** 4,060 L
- **EAN:** 4013456532885
- **ETIM40:** EC000414