

WALL LIGHTS

Wall Light REC L+



The PROLED WALL LIGHT REC series is designed for wall or step integration and offers various design possibilities in architectural illumination.

- incl. ABS plastic mounting sleeve

[PROLED WALL LIGHT REC L+ Manual](#)

325.3 KB

[EULUMDAT/IES information](#)

TECHNICAL DATA

IP classification:	IP65 (for outdoor use)
Power source:	220-240 VAC 50/60 Hz
Housing:	powder coated aluminium silver or white (RAL 9003)
Mounting sleeve:	ABS plastic
Electrical connection:	1x cable 0,5 m H05RN-F 3x 1,0 mm ² to open wires
Average lifetime:	50.000 h at L80/B10
Operating temperature range:	-10° C till +45° C

PHOTOMETRIC DATA

LED type:	SMD LEDs
Luminous flux:	housing silver: warm white 150 Lumen housing white: warm white 190 Lumen
Colour temperature:	warm white 3000 K

CRI:

80

Due to conditions of production photometric data can vary from production batch to production batch within the EU directive.

PRODUCT TYPES

order code	colour	housing	LED pcs	LED power	power consumption*	weight	EEL	
L17216LU	warm white	silver	20	4 Watt	7 Watt	1,05 kg	B	
L17216LUW	warm white	white	20	4 Watt	7 Watt	1,05 kg	A	

*Actual power consumption

© MBN GmbH

PROLED®

Member of PROLED GROUP