

292202EX

ATEX WATERTIGHT WALL-MOUNTING SWITCH IN THERMOSETTING ENCLOSURE 25A 3P LAYOUT 2 92x125 2PG16 IP67



Product data

Code ELECTROCOD:	2302
Series:	CAM-Ex
Min order quantity:	1
EAN code:	8014950007882
Weight:	0,859 KG

Reference standards and guidelines


Reference Standards:	EN 60529: 1997 + A1: 2000 EN 60947-3: 1999 + A1: 2001 + A2: 2005 EN 50014: 1997 + A1: 1999 + A2: 1999 EN 60079-15: 2003 EN 50281-1-1: 1998 + EC: 1999 + A1: 2002
----------------------	--

Marks:



Attachments


Dimensional (format .PNG):



Technical data

ATEX application zone:	Zona/Zone 2 and 22
Atex Dust Class:	II 3D Ex tc IIIC T85°C Dc IP66
Atex Gas Class:	II 3G Ex nR IIC T6 Gc

Hole type:




Protection level: IP67

CAM layout: 2

Container dimensions: 92X125

Front-plate:



Customs code: 8536 50 15 90

 Category of use ATEX
DUST: II 3D 100°C IP67

 Category of use ATEX
GAS: II 3G EEx nR T5

 Poles:
3

Manufacturing Material: Thermosetting

Nominal current: 25 A

DXF Drawing:  [292101.dxf](#)

Execution:	WALL MOUNTING
Product Class:	SWITCH
Shape:	RECTANGULAR
Protection:	NONE
Directive:	94/9/CE 2006/95/CE 2004/108/CE