## product sheet 47241909





47241909

ŝ



SCHUKO socket outlet with hinged cover with enhanced touch protection, Berker S.1, polar white matt

**Technical features** 

Design	according to DIN 4944
Main electrical features	
Nominal voltage	250
Rated current	16
Rated voltage	250 V A
Cover, door	
- Central cover plate	
Materials	
RAL colour	RAL 9010 - Pure whit
Colour of design line	polar whit
Colour	white
Colour	polarwhit
Material	duroplasti
Surface appearance	ma
-	
Installation, mounting - for flush-mounted and hollow-wall mounting Connection	
- for flush-mounted and hollow-wall mounting	according to IEC 60884-
- for flush-mounted and hollow-wall mounting Connection	-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> </ul>	according to IEC 60884- according to VDE 0620-
- for flush-mounted and hollow-wall mounting Connection Connection terminals Connection terminals	-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>with plug-in terminals</li> </ul>	-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>With plug-in terminals</li> <li>Use</li> </ul>	-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>Connection terminals</li> <li>with plug-in terminals</li> <li>Use</li> <li>with enhanced touch protection</li> </ul>	according to VDE 0620-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>Connection terminals</li> <li>with plug-in terminals</li> <li>Use</li> <li>with enhanced touch protection</li> <li>Safety</li> </ul>	according to VDE 0620
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>Connection terminals</li> <li>with plug-in terminals</li> <li>Use</li> <li>with enhanced touch protection</li> <li>Safety</li> <li>IK protection code against mecanical impacts</li> </ul>	according to VDE 0620-
<ul> <li>for flush-mounted and hollow-wall mounting</li> <li>Connection</li> <li>Connection terminals</li> <li>Connection terminals</li> <li>with plug-in terminals</li> <li>Use</li> <li>with enhanced touch protection</li> <li>Safety</li> <li>IK protection code against mecanical impacts</li> <li>Enhanced contact protection</li> </ul>	-

- Only suitable for splash-protected IP44 flush-mounted installation when used in conjunction with the corresponding sealing set.