


LED waterproof light fitting

MODUS PL 7000, wide body 1575mm, LED 840 , body PE, opal PC cover, IP65, driver 1200mA, emergency pack

Code: PL7000L2W4ND/NZ

EAN: 8596099001124



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes	Material housing:	Plastic
Suitable for wall mounting:	Yes	Suitable for surface mounting:	Yes
Rated ambient temperature (°C):	-10...+45		
Suitable for ceiling mounting:	Yes		
Made in Czech republic:	Yes		

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	7500
System power (W):	50	Luminaire efficacy (lm/W):	150
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	1575	Width (mm):	135
Height/depth (mm):	100	Built-in length (mm):	1100
Size version:	L	Weight (kg):	3,3

Elektrické vlastnosti

Protection class:	I	Voltage type:	AC
Autonomy (h):	1	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Suitable for emergency lighting:	Yes	No dim function:	Yes