



**Key change-over switch with imprint surface-mounted, isolated input terminals Lock - differing lockings, Key can be removed in 2 positions, Berker W.1, grey/light grey matt**

#### Technical features

#### Architecture

|                      |     |
|----------------------|-----|
| Type of control unit | Key |
|----------------------|-----|

#### Main electrical features

|                 |          |
|-----------------|----------|
| Nominal voltage | 240 V    |
| Rated voltage   | 240 V AC |

#### Electric current

|                   |      |
|-------------------|------|
| Switching current | 10 A |
|-------------------|------|

#### Materials

|                       |                      |
|-----------------------|----------------------|
| Colour of design line | grey/light grey      |
| Colour                | iron grey            |
| Colour                | dark grey            |
| RAL colour            | RAL 7011 - Iron grey |
| Material              | thermoplastic        |
| Surface appearance    | matt                 |

#### Dimensions

|        |       |
|--------|-------|
| Depth  | 64 mm |
| Height | 76 mm |
| Width  | 76 mm |

#### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

#### Connection

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with screw terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside
- for master-key systems

#### Use

|                                          |                                   |
|------------------------------------------|-----------------------------------|
| Differentiation characteristic 2 - Sales | Lock - differing lockings         |
| Differentiation characteristic 3 - Sales | Key can be removed in 2 positions |

#### Safety

|                     |      |
|---------------------|------|
| Protection index IP | IP55 |
| - with 2 keys       |      |

32713505



**IP55**

#### Use conditions

|                               |             |
|-------------------------------|-------------|
| Operating temperature         | -40...30 °C |
| Storage/transport temperature | -50...50 °C |

#### Identification

|                  |            |
|------------------|------------|
| Main design line | Berker W.1 |
|------------------|------------|

#### Instructions

|                  |                                          |
|------------------|------------------------------------------|
| Information text | Pins of quick-release lock made of ZAMAK |
|------------------|------------------------------------------|