



50463525



**Push-button insert, change-over contact, illuminated surface-mounted/flush-mounted with lens, Berker W.1, grey matt**

#### Technical features

##### Architecture

|                      |        |
|----------------------|--------|
| Type of control unit | rocker |
|----------------------|--------|

##### Main electrical features

|                 |       |
|-----------------|-------|
| Nominal voltage | 250 V |
|-----------------|-------|

|               |          |
|---------------|----------|
| Rated voltage | 250 V AC |
|---------------|----------|

##### Electric current

|                           |      |
|---------------------------|------|
| Momentary-contact current | 10 A |
|---------------------------|------|

##### Materials

|                       |      |
|-----------------------|------|
| Colour of design line | grey |
|-----------------------|------|

|        |           |
|--------|-----------|
| Colour | iron grey |
|--------|-----------|

|        |           |
|--------|-----------|
| Colour | dark grey |
|--------|-----------|

|            |                      |
|------------|----------------------|
| RAL colour | RAL 7011 - Iron grey |
|------------|----------------------|

|          |               |
|----------|---------------|
| Material | thermoplastic |
|----------|---------------|

|                    |      |
|--------------------|------|
| Surface appearance | matt |
|--------------------|------|

##### Dimensions

|       |       |
|-------|-------|
| Depth | 42 mm |
|-------|-------|

|        |       |
|--------|-------|
| Height | 71 mm |
|--------|-------|

|       |       |
|-------|-------|
| Width | 71 mm |
|-------|-------|

##### Installation, mounting

|                   |                     |
|-------------------|---------------------|
| Installation mode | for screw fastening |
|-------------------|---------------------|

##### Connection

- with plug-in terminals
- with N-terminal

##### Equipment

- with {b blue} 230 V LED unit
- for lighting and monitoring circuit

##### Use

|                                          |           |
|------------------------------------------|-----------|
| Differentiation characteristic 2 - Sales | with lens |
|------------------------------------------|-----------|

##### Safety

|                     |      |
|---------------------|------|
| Protection index IP | IP55 |
|---------------------|------|

##### Use conditions

|                       |             |
|-----------------------|-------------|
| Operating temperature | -40...30 °C |
|-----------------------|-------------|

#### Identification

|                    |                                       |
|--------------------|---------------------------------------|
| Application, usage | Surface-mounted wet-room installation |
| Main design line   | Berker W.1                            |

#### Instructions

|                                                                                                                                                                                            |                                          |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|
| Information text                                                                                                                                                                           | Pins of quick-release lock made of ZAMAK |
| <ul style="list-style-type: none"><li>- Inserts will only reach the degree of protection IP55 if mounted with a housing surface mounted or frame for flush-mounted installation.</li></ul> |                                          |