

MAGNUM FUTURE LED 32W



110 V | LED |  |  |  | IP44 | IP54 | IK10

TECHNICAL PARAMETERS

Ingress protection:	IP54; IP44;
Impact resistance:	IK10;
Rated power of the luminaire [W]*:	32.00;
Supply voltage [V]:	220-240; 24; 42-48; 110;
Luminous flux [lm]*:	4300;
Electrical protection class:	II; I; III;
Colour temperature [K]:	4000;
Beam angle [°]:	120;
Diffuser material:	PC;
Diffuser type:	frozen;
Material of the body:	PP;
Colour of the body:	grey;

*Tolerance +/- 10%

CHARACTERISTICS

Compact and light LED floodlight for professional use. It provides uniform and stable directional lighting. Luminaire made of impact-resistant polipropylene (PP). Anti-glare diffuser made of polycarbonat (PC) which, despite the matt surface, transmits up to 80% of the light emitted by the diodes. It is equipped with a multi-position arm with a tilt lock of the housing, handles for cable winding and an ergonomic carrying handle.
A rubber cable H07RN-F 3x1.5 mm² (3 m) comes as standard.

APPLICATION

The luminaire will provide precise illumination of the workplace.

MAGNUM FUTURE LED 32W

AVAILABLE TYPES

[Click >> index, to see details](#)

MAGNUM FUTURE LED 32W 110V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE	CEE	2		5			I	IP44	>> 247231

MAGNUM FUTURE LED 32W 220-240V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CH				5			II	IP44	>> 247217
32	4300	CH	CH	2		5			I	IP44	>> 247033
32	4300	CH	CH	2		5	yes	BACKLIGHT	I	IP44	>> 247118
32	4300	CH	CH	2		5	yes		I	IP44	>> 247071
32	4300	DK				5			II	IP44	>> 247224
32	4300	DK	DK	2		5			I	IP44	>> 247026
32	4300	DK	DK	2		5	yes	BACKLIGHT	I	IP44	>> 247101
32	4300	DK	DK	2		5	yes		I	IP44	>> 247064
32	4300	UNI-SCHUKO				5			II	IP54	>> 247200
32	4300	UNI-SCHUKO	PL-FR	2		5	yes	BACKLIGHT	I	IP54	>> 247088
32	4300	UNI-SCHUKO	PL-FR	2		5			I	IP54	>> 247309
32	4300	UNI-SCHUKO	PL-FR	2		5	yes		I	IP54	>> 247040
32	4300	UNI-SCHUKO	SCHUKO	2		5	yes	BACKLIGHT	I	IP54	>> 247095
32	4300	UNI-SCHUKO	SCHUKO	2		5			I	IP54	>> 247019
32	4300	UNI-SCHUKO	SCHUKO	2		5	yes		I	IP54	>> 247057

MAGNUM FUTURE LED 32W 24V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE				5			III	IP44	>> 247262
32	4300	CEE	CEE (2-PIN)	2		5			III	IP44	>> 247279
32	4300	TRAFO				5			III	IP44	>> 247286

MAGNUM FUTURE LED 32W 42-48V

Nominal power [W]	Luminous flux [lm]*	Plug type	Socket type	Sockets	Wire type	Cable length [m]	Switch	Version	Electrical protection class	Ingress protection	Index
32	4300	CEE				5			III	IP44	>> 247248
32	4300	CEE	CEE (2-PIN)	2		5			III	IP44	>> 247255

*Tolerance +/- 10%

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer.

Revision date: 2020-11-12



Lena Lighting S.A.
ul. Kórnicka 52
63-000 Środa Wielkopolska

tel. +48 61 28 60 300
e-mail: office@lenalighting.pl
www.lenalighting.pl



The luminaire complies with the EU ROHS Directive 2011/65/UE



This product is a subject to electric and electronic waste equipment regulations (WEEE).



176/2018; 75/2020