


Cable Ties Polyamide 6.6 standard T18L



T-Series in PA66 natural, Article number: 111-02019

- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

These cable ties are used for routing, bundling and securing of cables, pipes and hoses.



Base Data

Application Tool	MK3SP, MK3PNSP2, MK7P, EVO7, MK20
Colour	Natural (NA)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T18L PA66 NA 100
Product Family	T-Series in PA66 natural
Product Group	Cable Ties Polyamide 6.6 standard
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T18L.NN3P
Variant	Inside Serrated

Product Dimensions

Bundle Ø max.	55.0 mm
Bundle Ø max. (imperial)	2.17 "
Bundle Ø min.	1.5 mm
Bundle Ø min. (imperial)	.06 "
Length (L)	205 mm
Length (L) (imperial)	8.0 "
Min. Tensile Strength (lbs)	18 lbs
Min.Tensile Strength (N)	80 N
Width (W)	2.5 mm
Width (W) (imperial)	.10 "

Logistic and Packaging

EAN / GTIN	5022660018749
Pack Cont.	100
Quantity per	Bag
Weight	0.3 kg

Material and Specifications

Flammability	UL94 V2
Halogenfree	Yes
Material	PA66
Material	Polyamide 6.6 (PA66)
Operating Temperature	-40 °C to +85 °C, (+105 °C, 500 h)
Specification	UL ZODZ2.E64963, DIN 30015955, GL 86 137-81 HH, BV 03856/H0 BV, Det Norske Veritas