

SLC SMARTONE AC DIMMER MINI

200W ZIGBEE LN

ZigBee AC phase-cut dimmer based on the latest Zigbee 3.0 protocol that supports Touchlink communication with Zigbee remotes. 200W (LED) / 400W (incandescent light/fluorescent light).



SLC Scandinavian
Lighting Concept

SmartOne



Technical data	
Product ID	S24013
CE	Yes
Exterior color	White
Dimming curve (LED)	Logarithmic
Dimming range	0-100% %
Flicker free	Yes
Operating temperature	-20°C ~ +45°C °C
Expected lifetime (Ta 25°C)	110000 Hours
Expected lifetime (Ta 45°C)	50000 Hours
RoHs	Yes
Tc	75 °C
Method of operation	Other
Colour	Black
Halogen free	Yes
Surface protection	Untreated
Material quality	Thermoplastic
Type of load	Universal and LED Retrofit
Material	Plastic
Light value memory	Yes
Applicable with movement sensor	Yes
Applicable with transmission button	Yes
Applicable with presence indicator	Yes
Applicable with button	Yes
Applicable with time switch/timer	Yes
Surface finishing	Matt
Dimming phase cut-off	Yes
Dimming method	Trailing edge
Dimming interface	Zigbee
Input	
Nominal voltage	100 - 240 V
Frequency	50 - 60 Hz
Output	

13.07.2020

Subject to changes and printing errors

Max total output power	200 W
Control voltage	100 - 240 V
Mono	Yes
Installation	
Mounting method	Built-in installation
Connection type	Screwed terminal
Min. depth of built-in installation box	31 mm
Type of fastening	Other
Core cross section	0.75 - 1.5 mm ²
Width of device	45.5 mm
Height of device	20.3 mm
Depth of device	45 mm
logistics data	
Imported by	The Light Group
Brand	SLC
General data	
Assembly arrangement	Basic element
Suitable for degree of protection (IP)	IP20