

# SWITCHING POWER SUPPLIES

## Switching Power Supplies

PROLED®



Power supplies with MM-sign and F-sign. Can be mounted on inflammable subsurface. Noiseless – without fan.

[PROLED SWITCHING POWER SUPPLIES General Manual](#)










187.4 KB 

[> 5 years warranty information](#)

### TECHNICAL DATA

Frequency range: 50/60 Hz


### PRODUCT TYPES

order code	output voltage	power	MM	power source	dimensions (l x w x h)	weight	
<b>L52012202G</b>	12 VDC	20 Watt	yes	220-240 VAC	113 x 44 x 28 mm	0,10 kg	
<b>L5201236</b>	12 VDC	40 Watt	yes	220-240 VAC	166 x 52 x 24 mm	0,19 kg	
<b>L5201250</b>	12 VDC	50 Watt	yes	220-240 VAC	184 x 61 x 32 mm	0,30 kg	
<b>L5201210</b>	12 VDC	100 Watt	yes	100-240 VAC	184 x 61 x 32 mm	0,33 kg	
<b>L52024202G</b>	24 VDC	20 Watt	yes	220-240 VAC	113 x 44 x 28 mm	0,10 kg	
<b>L5202436</b>	24 VDC	40 Watt	yes	220-240 VAC	166 x 52 x 24 mm	0,19 kg	
<b>L5202450</b>	24 VDC	50 Watt	yes	220-240 VAC	184 x 61 x 32 mm	0,25 kg	
<b>L5202475</b>	24 VDC	75 Watt	yes	220-240 VAC	184 x 61 x 32 mm	0,26 kg	
<b>L5202410</b>	24 VDC	100 Watt	yes	100-240 VAC	184 x 61 x 32 mm	0,32 kg	

---

order code	output voltage	power	MM	power source	dimensions (l x w x h)	weight
L52024150	24 VDC	150 Watt	yes	220-240 VAC	210 x 67 x 34 mm	0,55 kg

---



---

© MBN GmbH

# PROLED®

Member of PROLED GROUP