

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Shield connection clamp, connection method: Spring-cage connection, mounting type: NS 35/7,5, NS 35/15, color: black

Your advantages

- Convenient single-handed installation
- Shield connection clamps for cable diameters up to 20 mm
- Modern spring technology protects against vibrations
- Low transfer impedance due to large-surface shield connection
- High corrosion resistance
- Unique marking surface for cable designations
- As components, it is not possible to certify shield connections in accordance with the requirements of the directive and standards for electrical equipment in potentially explosive areas. As such, shield connection clamps can be used in the Ex area even without an appropriate approval or marking.

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Commercial Data

Item number	1019446
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	BE7523
Product Key	BE7523
GTIN	4055626506159
Weight per Piece (including packing)	49.13 g
Weight per Piece (excluding packing)	48.4 g
Customs tariff number	85369010
Country of origin	CN

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Technical Data

Product properties

Product type	Shield connection clamp
Number of positions	1

Connection data

Stripping length	50 mm
------------------	-------

Dimensions

Width	24.7 mm
Height	52.4 mm
Height NS 35/15	61.9 mm
Height NS 35/7,5	54.4 mm
Length	45.9 mm

Material specifications

Color	black
Flammability rating according to UL 94	V0
Insulating material group	CTI 600
Insulating material	PA 6.6
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Connector

Number of positions	1
Number of positions	1
Number of positions	1

Cable / line

Cable structure

External cable diameter	10 mm ... 20 mm
-------------------------	-----------------

Mechanical tests

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Mechanical strength

Result	Test passed
--------	-------------

Attachment on the carrier

DIN rail/fixing support	NS 32/NS 35
Result	Test passed

Environmental and real-life conditions

Needle-flame test

Time of exposure	30 s
Result	Test passed

Oscillation/broadband noise

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Spectrum	Service life test category 2, bogie-mounted
Frequency	$f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$
ASD level	$6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$
Acceleration	3.12g
Test duration per axis	5 h
Test directions	X-, Y- and Z-axis
Result	Test passed

Shocks

Specification	DIN EN 50155 (VDE 0115-200):2018-05
Pulse shape	Half-sine
Acceleration	30g
Shock duration	18 ms
Number of shocks per direction	3
Test directions	X-, Y- and Z-axis (pos. and neg.)
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C
Permissible humidity (storage/transport)	30 % ... 70 %

Mounting

Mounting type	NS 35/7,5
	NS 35/15

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Classifications

ECLASS

ECLASS-9.0	27141150
ECLASS-10.0.1	27141150
ECLASS-11.0	27141150

ETIM

ETIM 8.0	EC002020
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Accessories

Label

Label - EML (10X4)R - 0815583

<https://www.phoenixcontact.com/gb/products/0815583>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 10 x 4 mm, Number of individual labels: 10000

Label

Label - EML (10X7)R - 0816663

<https://www.phoenixcontact.com/gb/products/0816663>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 10 x 7 mm, Number of individual labels: 10000

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Label

Label - EML (15X6)R - 0803275

<https://www.phoenixcontact.com/gb/products/0803275>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 15 x 6 mm, Number of individual labels: 2500

Label

Label - EML (15X9)R - 0815677

<https://www.phoenixcontact.com/gb/products/0815677>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 15 x 9 mm, Number of individual labels: 2500

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Label

Label - EML (16,5X5)R - 0816702

<https://www.phoenixcontact.com/gb/products/0816702>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 16.5 x 5 mm, Number of individual labels: 2500

Label

Label - EML (16X7)R - 0818001

<https://www.phoenixcontact.com/gb/products/0818001>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMaster 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 16 x 7 mm, Number of individual labels: 10000

Shield connection clamp - SCC 20-NS35



1019446

<https://www.phoenixcontact.com/gb/products/1019446>

Label

Label - EML (17,5X8)R - 0816744

<https://www.phoenixcontact.com/gb/products/0816744>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 17.5 x 8 mm, Number of individual labels: 2500

Label

Label - EML (19X6)R - 0816760

<https://www.phoenixcontact.com/gb/products/0816760>



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK ROLL X1, THERMOMARK ROLL 2.0, THERMOMARK ROLL, mounting type: adhesive, lettering field size: 19 x 6 mm, Number of individual labels: 2500

Phoenix Contact 2022 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd
Halesfield 13, Telford
Shropshire, TF7 4PG
01952 681700
info@phoenixcontact.co.uk