

PRODUCT-DETAILS

MLBL-07BW

MLBL-07BW LED block



G	en	er	al	Inf	or	m	at	io	n
_	٠	•	۰.	••••	٠.	•••	~ ~		•

Extended Product Type	MLBL-07BW
Product ID	1SFA611621R2075
EAN	7320500545454
Catalog Description	MLBL-07BW LED block

Long Description

The MLBL-07BW LED block is: - White - Illuminated - Rear mounting - 230 V
This LED block is part of ABB's modular plastic range, the most versatile range with a
high level of flexibility and market-leading electrical ratings. Engineered for total
reliability, longer lifetime, and highest mechanical durability. Self-cleaning contacts
ensure reliable operation without the need for maintenance, increasing uptime. A high
degree of protection guarantees reliability in extreme environments. The innovative
design simplifies the entire process, from selection to easy and quick, tool-free
installation. The perfect solution for every application.

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85369001

Popular Downloads

Data Sheet, Technical Information	1SFC151007C02_
Instructions and Manuals	1SFC151011M0201

MLBL-07BW 2

Dimensions	
Product Net Width	0.01 m
Product Net Height	0.044 m
Product Net Depth / Length	0.042 m
Product Net Weight	0.01 kg
Technical	
Ambient Air Temperature	Operation -25 +70 °C Storage -40 +85 °C
Color	White
Illumination	Illuminated
Lamp Type	230 V AC, integrated LED
Mounting Type	Rear mounting
Degree of Protection	Terminals IP20
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	230 V AC
Connecting Capacity	Flexible with Ferrule 1 x 0.752.5 mm² Flexible with Ferrule 2 x 0.752.5 mm² Flexible with Insulated Ferrule 1 x 0.752.5 mm² Flexible with Insulated Ferrule 2 x 0.752.5 mm² Flexible 1 x 0.75 2.5 mm² Flexible 2 x 0.75 2.5 mm² Solid 1 x 0.752.5 mm² Solid 2 x 0.752.5 mm²
Connection Type	Screw Clamp
Terminal Type	Screw Clamp Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm
Suitable For	MCBH-00 MCBH5-00 MP1 MP1 MP2 MP3 MP4 MPMT3 MPMT3 MPMP3 M2SS1 M2SS2 M2SS3 M2SS4 M2SS5 M2SS6 M3SS1 M3SS1 M3SS2 M3SS3 M3SS4 M3SS5 M3SS5 M3SS5 M3SS5 M3SS5 M3SS5
Suitable for Product Class	MPM1 Pilot Devices

Technical UL/CSA Connecting Capacity UL/CSA 1x 18...14 AWG 2x 18...14 AWG

Environmental			
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019		
RoHS Date	0635 4		
RoHS Information	2CMT2015-005452		
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)		
WEEE B2C / B2B	Business To Business		

Certificates and Declarations (Document Number)		
CB Certificate	SEMKO_SE-56219	
CQC Certificate	CQC2008010305274953	
cULus Certificate	9AKK107046A9925	
Declaration of Conformity - CCC	2020980305001106	
Declaration of Conformity - CE	2CMT2015-005452	
DNV GL Certificate	E-14107	
EAC Certificate	1SFC150017D1101	
Environmental Information	1SAC200078H0001	
Instructions and Manuals	1SFC151011M0201	
RoHS Information	2CMT2015-005452	

Container Information		
Package Level 1 Units	bag 10 piece	
Package Level 1 Width	0.135 m	
Package Level 1 Depth / Length	0.155 m	
Package Level 1 Height	0.025 m	
Package Level 1 Gross Weight	0.11 kg	
Package Level 1 EAN	7320500373910	

Classifications	
Object Classification Code	E
ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
ETIM 8	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39121500
E-Number (Finland)	2315829
E-Number (Sweden)	3705682

Categories

MLBL-07BW 4

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products\ \rightarrow Pilot\ Devices \rightarrow Accessories$ $Low\ Voltage\ Products\ and\ Systems \rightarrow Control\ Products\ \rightarrow Pilot\ Devices \rightarrow Modular\ Plastic\ Range$

