



SLC CUP R62 BL 649TED 2700K CRI90 IP20 36°

12/01/2023

3234533



Product description

SLC Design Cup is a recessed ceiling luminaire unique due to its shape and appearance. Cup has a character that withstands time and trends. SLC Design Cup is elegant - both visually and technically: The housing is in a matt colour, and the interior has a metallic finish. SLC Design Cup is ideal for focus lighting with its tilt and rotation function. It creates visible effects in the illumination of objects, pictures and furniture.

SLC Design Cup is a recessed ceiling luminaire unique due to its shape and appearance. Cup has a character that withstands time and trends. SLC Design Cup is elegant - both visually and technically: The housing is in a matt colour, and the interior has a metallic finish.

SLC Design Cup is ideal for focus lighting with its tilt and rotation function. It creates visible effects in the illumination of objects, pictures and furniture. A deep built-in chip reduces glare and provides pleasant ambient light and a lively atmosphere. Do you want an individual design change? Try out a variety of cup inner rings (see next page).

Dimmable (TED) driver included
Recommended dimmer: SLC SmartOne (S24019)
Can be tilted 40° and rotated 350° in all directions
CRI Ra>90 enhances vivid colours in any environment
Quick connection box with Loop-in / Loop-Out



Technical data

Suitable for built-in mounting	Yes
Suitable for suspended mounting	No
Adjustability	Rotating and swivelling
With light source	Yes
Surface protection	Powder coating
Material cover	Plastic, transparent
Nominal voltage	220 - 230 V
Type of control gear	LED operating device current-controlled


Suitable for wall mounting	No
Suitable for ceiling mounting	Yes
Lamp type	LED not exchangeable
Material housing	Aluminium
Colour housing	Black
Voltage type	AC/DC
LED nominal current at constant current	230 - 230 mA
Control gear included	Yes






Dimming phase cut-off	Yes
Light distributor	Reflector
Beam angle	Medium beam 21-40°
Rated life time L90/B10 at 25 °C	50000 h
Protection class	II
Max. system power	9 W
Colour temperature	2700 - 2700 K
Luminous flux	649 - 649 lm
Lamp efficacy	72,1 lm/W
Width	61 mm
Length	61 mm
Built-in height/depth	43 mm
Built-in diameter	62 mm
Number of poles	3
Connectable conductor cross section	0,25 - 1,5 mm ²
Luminaire efficacy	72,22 lm/W
Colour rendering index (CRI/Ra)	90
Cut-out hole (Ø: mm)	62
Type of control signal	Amplitude modulation (AM)
GTIN	7070938063623
HS Code	94051040


Reflector	High-gloss
Light sharing	Symmetric
Light outlet	Direct
Degree of protection (IP)	IP20
Rated ambient temperature according to IEC	-10 - 45 °C
Colour of light	White
Colour rendering index CRI	90-100
Rated luminous flux according to IEC 62722-	649 lm
Power factor	0,95
Height/depth	103 mm
Built-in width	62 mm
Built-in length	62 mm
Type of wiring	Suitable for through wiring
Conductor cross section	0,35 mm ²
Connection type	Plug clamp
Colour consistency (McAdam ellipse)	SDCM3
Beam angle (°)	36
Dimming method	Trailing edge
Brand	SLC
Produced by	The Light Group
RAL Colour	RAL9005





Scandinavian Lighting Concept

3234533



11
kWh/1000h



2019/2015

