



**SERIES TOP-TER
SOCKET OUTLET
CODE 579840**



Datasheet

Electrical characteristics

Rated current	10/16A
Supply Voltage	250V~ 50/60Hz
Poles	2P+ $\perp$
Clock Position	-
Rated insulation voltage	-
Signal plug inserted	-

Reference Standards and Directives

Certification and approval marks	CE
Directives	2011/65/EU (RoHS), 2001/95/EC (GPSD), 2012/19/EU (WEEE)
Reference Standards	CEI 23-50/V1:2008, CEI 23-50:2007, CEI 23 50/V3:2015, CEI 23-50/V4:2015, IEC 60884 1/A1:2006, EN 63000:2018, CEI 23 50/V2:2011, IEC 60884-1:2002, IEC 60884 1/A2:2013

Mechanical characteristics

Manufacturing material	Technopolymer Recyclable Palazzoli
Alveolus/plugs treatment	-
Color	Grey RAL 7035
Tightening diameter	-
Execution	Panel mounting
Protection degree	IP66
Additional degree protection	-
Shock resistance	IK08 according to IEC/EN 62262
Resistance to Glow wire	850°C (Socket), 650°C (Box)
Flame rating according UL94	V-2 (Socket), HB (Box)
Terminals type	Screw - indirect clamping
Conductors section	Min: 1 mm ² ;Max: 2,5 mm ²
Terminal tightening torque	0,8 Nm
Net Weight	0.079 KG
Working Environment Temp.	Min: -25°C ;Max: +50°C
Warehousing Temperature	Min: -30°C ;Max: +70°C

The images are purely indicative. Palazzoli reserves the right to make changes without notice.