



SLC Power Supply CV RF 24V 50W PWM PushDim

02/02/2023

S32001



Product description

50W Power supply with built-in PWM-dimmer. Mono.

50W Power supply with built-in PWM-dimmer. Mono. Dimmable both with PushDim and different remote controls, making this a simple and practical power supply for single-coloured lighting. Protection against overload, short circuit and overheating. For 24V LED-strips and other products with 24V operating voltage

Technical data

Model	Static
Dimming 0-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming GPRS	No
Dimming manufacturer's proprietary system	No
Dimming phase cut-off	No
Dimming programmable	No
Dimming Sine Wave Reduction	No
Dimming Zigbee	No
No dim function	No
Suitable for constant current	No
Output voltage	24 - 24 V
Suitable for DC-voltage (primary side)	No
Degree of protection (IP)	IP20

Suitable for outdoor use	No
Dimming 1-10 V	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming phase cut-on	No
Dimming RF	Yes
Dimming Touch and Dim	No
Dimming with push-button	Yes
Housing	Plastic housing
Suitable for constant voltage	Yes
Output current	208 - 2080 mA
Output power	5 - 50 W
Protection class	II





Length	210 mm
Height	32 mm
Number of LED Output Channels	1
Mono	Yes
RGB	No
Electrical connection (Out)	L`N quick connection
Frequency range (Hz)	50 - 60
Strain relief	Yes
Operating temperature	-20°C ~ +45°C
Dimming method	Pulse Width Modulation (PWM)
Brand	SLC
Produced by	The Light Group

Width	50 mm
Output type	Constant voltage (CV)
Output power per channel (W)	5 - 50
Tunable White	No
RGBW	No
Input voltage (V)	100 - 240
Power factor	0,9
Exterior color	White
Expected lifetime (Hours) (Ta 45°C)	50000
Dimming interface	RF (Radio Frequency) 869,5MHz, PushDim
GTIN	7070938057189
HS Code	85044082

