

TIG15323 Fan heater

Article number: 271753



Description

Robust fan heater for portable use in demanding environments

Tiger is a range of robust and compact fan heaters for professionals with high demands. The Tiger fan heater has a compact and robust sheet steel design with a red finish. The heavy-duty tubular frame acts as a well-balanced and ergonomic carrying handle. The design protects against impact and vibrations and permits use in exacting environments.

Technical parameters

| Nominal data                                           |               |       |
|--------------------------------------------------------|---------------|-------|
| Color casing                                           | Traffic red   |       |
| Color casing, NCS                                      | NCS 1090-Y80R |       |
| Color casing, RAL                                      | RAL 3020      |       |
| Enclosure class                                        | IP44          |       |
| Ambient working temperature (dry conditions)           | -25 to 40     | °C    |
| Dimensions and weights                                 |               |       |
| Width                                                  | 410           | mm    |
| Height                                                 | 510           | mm    |
| Depth                                                  | 530           | mm    |
| Weight                                                 | 17            | kg    |
| Air flow                                               |               |       |
| Air flow                                               | 1,120         | m³/h  |
| Air flow                                               | 1,120         | m³/h  |
| Sound data                                             |               |       |
| Sound level                                            | 53            | dB(A) |
| Motor/control supply                                   |               |       |
| Control/motor supply                                   | 230           | V     |
| Control/motor current                                  | 0.47          | A     |
| Frequency                                              | 50; 60        | Hz    |
| Electric heat                                          |               |       |
| Input power, heater                                    | 7.5; 15       | kW    |
| Current heating                                        | 18; 37.5      | A     |
| Voltage heating                                        | 230           | V     |
| Phases                                                 | 3~            |       |
| Temperature rise, maximum heat output, highest airflow | 41            | °C    |

Accessories

LT22406 Bracket (220400)

Documents

Catalogue pages Tiger  
Manual Tiger 2-15  
Declaration of Conformity Tiger TIG1523