

NAIL PLASTER | GEMINI

HIGH-ADHESION NAIL POINT SEALANT TAPE

HERMETIC

The closed cell polyethylene structure ensures the opening created by the fastening systems is waterproof.

WIDE RANGE

Also available in 5 mm thickness, 70 mm width and double-sided adhesive for more secure sealing.

COMPOSITION

NAIL PLASTER

carrier
PE foam

adhesive
synthetic rubber

GEMINI

adhesive
synthetic rubber

carrier
PE foam

adhesive
synthetic rubber

liner
silicone-impregnated film

CODES AND DIMENSIONS

NAIL PLASTER

CODE	B [mm]	s [mm]	L [m]	B [in]	s [mil]	L [ft]	
NAILPLA350	50	3	30	2.0	118	98	10
NAILPLA370	70	3	30	2.8	118	98	7
NAILPLA550	50	5	10	2.0	197	33	6

CODE	B [mm]	H [mm]	s [mm]	B [in]	H [in]	s [mil]	pcs/roll	
NAILPLA35050	50	50	3	2.0	2.0	118	400	6

GEMINI

CODE	B [mm]	s [mm]	L [m]	B [in]	s [mil]	L [ft]	
GEMINI60	60	3	30	2.4	118	98	8
GEMINI80	80	3	30	3.2	118	98	6

TECHNICAL DATA

Properties	standard	value	USC conversion
Tensile strength	EN 1939	material failure	
Temperature resistance	-	-30 / +80 °C	-22 / +176 °F
Application temperature	-	≥ +5 °C	≥ +41 °F
Storage temperature ⁽¹⁾	-	+5 / +25 °C	+41 / +77 °F
Solvents	-	no	-

⁽¹⁾Store the product in a cool, dry place for no more than 12 months.
Waste classification (2014/955/EU): 08 04 10.

FIELDS OF APPLICATION



PRACTICAL

With the help of LIZARD, installation is easy and fast, done directly on the ventilation battens.

DOUBLE SECURITY

The GEMINI version offers double adhesiveness and guarantees continuous adhesion between the membrane and batten, avoiding water accumulation in drilled points.