


PRODUCT-DETAILS

OT1250E03CP

OT1250E03CP CHANGE-OVER SWITCH



General Information

Extended Product Type	OT1250E03CP
Product ID	1SCA022872R0790
EAN	6417019338897
Catalog Description	OT1250E03CP CHANGE-OVER SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

Circular Value

Conflict Minerals Reporting Template (CMRT)	9AKK108467A5658
Environmental Information	1SCC303050D0201
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Ordering

Minimum Order Quantity	1 piece
------------------------	---------

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301049M0002

Dimensions

Product Net Width	400 mm
Product Net Height	306 mm
Product Net Depth / Length	309 mm
Product Net Weight	48 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 1250 A (500 V) 1250 A (690 V) 1250 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 1250 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 1250 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 710 kW (500 V) 900 kW (690 V) 1200 kW
Conventional Free-air Thermal Current (I_{th})	$\Theta = 40\text{ °C}$ 1250 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 50 kiloampere rms
Power Loss	29 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism at the End of the Switch 03 (Left Side)

Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Terminal Width	50 mm
Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
Transition Type	Open

Technical UL/CSA

Tightening Torque	acc. IEC 60947-1 50 ... 75 N·m
-------------------	--------------------------------

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Environmental Information	1SCC303050D0201

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303016D0201
Environmental Information	1SCC303050D0201
Instructions and Manuals	1SCC301049M0002
REACH Declaration	1SCC011021D0201
RoHS Information	1SCC011020D0201

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	500 mm
Package Level 1 Depth / Length	600 mm
Package Level 1 Height	550 mm
Package Level 1 Gross Weight	51 kg
Package Level 1 EAN	6417019338897

Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter

ETIM 9	EC000216 - Switch disconnecter (low voltage)
eClass	V11.1 : 27371403
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3600147

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

