

Data sheet

Commercial Art.No.: 92.257.2003.9

cable assembly GST18i5K1B- 15 20PB02

GST18i5 connection cable, female - free end, number of poles 5, rated voltage 250 V / 400 V, rated current 16 A, cable type H05VV-F, fire class Eca, total length 2 m, nominal cross section conductor 1.5 mm², color of coding/ contact carrier pastel blue



Commercial Art.No.	92.257.2003.9
EAN	4015573611535
Order Unit	1

certificates / approvals



Technical data

general

rated current	16 A
rated voltage	250 V / 400 V
rated impulse voltage	4 kV
pollution degree	2
mechanical coding	code 2
continuity resistor	23.2 mOhm
lockable	self-locking (unlocking by tool)
color of coding/ contact carrier	pastel blue
marking of poles	L, N, PE, D1, D2
color of housing inclusive strain relief	black

model

nominal cross section conductor	1.5 mm ²
degree of protection (IP)	IP40
wire strip length	9 mm
sheath strip length	35 mm
preparation of conductor ends	ultrasonically compressed wire ends
cable type	H05VV-F
cable color	black
cable diameter max.	10.1 mm
version of cable	female - free end
type of cord set	connection cable

version cable end 1	GST18i5 female
version cable end 2	free end

material

surface finish	tin-plated
halogen free	no
continuous temperature of cable	70 °C
insulation components continuous temperature	100 °C
fire load	1.344 kWh
fire class	Eca

dimensions

total length	2 m
--------------	-----

classification

ECLASS 11	
ECLASS 8.1	27440604
ETIM 9.0	EC002587
ETIM 8.0	EC002587
ETIM 7.0	EC002587
ETIM 6.0	EC002587
ETIM 5.0	EC002587
ETIM 4.0	EC002587

product compliance



ROHS conformity status	compliant/exempted
ROHS exceptions	III-6(c)
REACH-SVHC conformity status	Duty-To-Declare
REACH-SVHC substances	Lead
REACH-SVHC CAS numbers	7439-92-1

Accessories

Commercial Art.No.:	Article-type description:	Description:
05.587.3156.0	lock (G)ST18 WS	Locking device for cable to cable connection GST18i3-5, white
05.564.5353.0	cover cap GST18i3/4/5 SW	Cover piece 12 pole black for female parts GST18i3-6
05.564.5353.2	cover cap GST18i3/4/5 WS	Cover piece 12 pole white for female parts GST18i3-6
05.566.9253.0	cover cap GST18i5 BUCHSEN	Cover for female connectors GST18i5, black
05.587.3156.1	lock (G)ST18 SW	Locking device for cable to cable connection GST18i3-5, black

These dimensions will be especially checked at delivery
Only inspection dimensions
With /E marked dimensions are only valid for internal use

Diese Maße werden bei Abnahme besonders geprüft
Ausschließlich Prüfmaße
Mit /E gekennzeichnete Maße sind nur für interne Zwecke gültig



Typ/type: GST1815KSB 15 ..PB02

Einsatz-Farbe insert colour	Codierung "X" Buchse female	Kabelfarbe cable colour
Pastellblau pastel blue	L N PE D2 D1 	schwarz black

Teile-Nr. part-no.	L	Beispiel (Farbe: pastelblau) exampel (colour: pastel blue)	Typ type
92.257.XX03.9	XX in dm-Schritten	92.257.1003.9 = 10dm/L= 1000mm	GST1815KSB 15 10PB02
U2.257.XX03.9	XX in m-Schritten	U2.257.1203.9 = 12 m/L=12000mm	GST1815KSB 15 X12PB02
Tolerierung nach DIN 7167/Tolerance system acc. to DIN 7167. (This DIN-standard describes the envelope principle. According to the envelope principle the deviations of form and parallelism are limited by the size tolerances).		ja/yes ☒ Stoffverbots- und Deklarationsliste nach UU-TQM-05/03 ist einzuhalten. Conformity with Wieland document UU-TQM-05/03 (list of prohibited / declarable hazardous substances) to be declared!	
Freitoleranz nach General tolerance		CAD - Zeichnung, keine manuellen Änderungen CAD - drawing, no manual modifications allowed	1.Verwendung: - First Use:
		Werkstoff/Material	Blatt: 1 von 1 Sheet: of 1
		2008 gezeichnet drawn 24.07. geprüft checked Normgepr. Stand. check	Name Dütsch T.
		Maßstab/Scale	Zeichnung Nr./Drawing No.
		Vol. mm ³ Dtl./Surf. mm ²	Index a
		Ersatz für/Replacement for: -	
		Type	Benennung/Title
		PRE-ASSEMBLED CABLE KONFEKT_LEITUNG	
		Buchse/female Schraubanschluß/screw connection 250/400V 1,5qmm	

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet.
The reproduction, distribution and utilization of this document as well as the communication of its contents to others without express authorization is prohibited.