

PRODUCT-DETAILS

E 9F22 AM63

E 9F22 AM63 Fuse link



General Information

Extended Product Type	E 9F22 AM63
Product ID	2CSM258233R1801
EAN	8012542582335
Catalog Description	E 9F22 AM63 Fuse link
Long Description	E 9F22 AM63 is a 22x58 mm cylindrical fuse for motors protection

Technical

Standards	IEC 60269-2
Rated Voltage (U_r)	690 V
Rated Current (I_n)	63 A
Maximum Breaking Capacity	120 kA
Power Loss	at Rated Operating Conditions per Pole 4.8 W
Fuse Type	aM
Release Type	aM: Used in short-circuit protection of motor circuits
Construction Material	Ceramic
Fuse Size	22x58
Contact Material	copper silver plated (Cu/Ag)

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK106713A5625

REACH Declaration	9AKK108467A9482
Environmental Information	See RoHS Information
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Product Net Width	0.002 m
Product Net Height	0.006 m
Product Net Depth / Length	0.002 m
Product Net Weight	0.048 kg

Ordering

Minimum Order Quantity	10 piece
Package Level 1 Units	box 10 piece
Package Level 1 Gross Weight	0.05 kg
Customs Tariff Number	85361050
Country of Origin	Tunisia (TN)

Certificates and Declarations

Cut-off Current Characteristic	9AKK108466A9073
Declaration of Conformity - CE	9AKK106713A5625
I ² t Characteristic	9AKK108467A0129

Popular Downloads

Data Sheet, Technical Information	9AKK107991A8329
Instructions and Manuals	No document needed
Cut-off Current Characteristic	9AKK108466A9073
Dimension Diagram	9AKK108466A8534
I ² t Characteristic	9AKK108467A0129
Time-Current Characteristic Curve	9AKK108467A0150

Classifications

ETIM 8	EC002704 - Cylindrical fuse
ETIM 9	EC002704 - Cylindrical fuse
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85361050
eClass	V11.0 : 27142002
Object Classification Code	F

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Protection and Safety Devices → Cylindrical and D0 Fuses

