

## PRODUCT-DETAILS

# B6-30-10-P-01

## B6-30-10-P-01 Mini Contactor 24 V AC - 3 NO - 0 NC - Soldering Pins



### General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | B6-30-10-P-01   |
| Product ID            | GJL1211009R0101   |
| EAN                   | 4013614051623   |
| Catalog Description   | B6-30-10-P-01 Mini Contactor 24 V AC - 3 NO - 0 NC - Soldering Pins   |
| Long Description      | The B6-30-10-P mini contactor is a compact 3 pole contactor with 1 auxiliary contact and soldering pins. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the silent coil, a switch position indication and the integrated possibility for rail mounting. |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85365080 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100214C0202 |
| Instructions and Manuals          | 2CDC102047M6801 |
| CAD Dimensional Drawing           | 2CDC001079B0201 |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 47.5 mm |
| Product Net Height         | 45.2 mm |
| Product Net Depth / Length | 47.7 mm |
| Product Net Weight         | 0.17 kg |

## Technical

|   |  |
|---|--|
| Number of Poles   | 3  |
| Mini Contactor Type   | Mini Contactor   |
| Rated Operational Voltage                                   | Auxiliary Circuit 690 V AC<br>Auxiliary Circuit 250 V DC<br>Main Circuit 690 V AC<br>Main Circuit 220 V DC   |
| Rated Frequency (f)   | Control Circuit 400 Hz<br>Control Circuit 50 Hz<br>Control Circuit 60 Hz<br>Main Circuit 60 Hz<br>Main Circuit 50 Hz<br>Main Circuit DC                |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | Auxiliary Circuit 6 kV<br>Main Circuit 6 kV  |
| Rated Insulation Voltage ( $U_i$ )                          | 690 V<br>acc. to UL/CSA 600 V  |
| Number of Main Contacts NC                                  | 0  |
| Number of Main Contacts NO                                  | 3  |
| Rated Operational Current AC-1 ( $I_e$ )                    | (220 / 240 V) 40 °C 12 A<br>(220 / 240 V) 55 °C 12 A<br>(380 / 440 V) 40 °C 12 A<br>(380 / 440 V) 55 °C 12 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |
| Rated Operational Power AC-3 ( $P_e$ )                      | (230 V) Three Phase 2.2 kW<br>(400 V) Three Phase 4 kW<br>(500 V) Three Phase 4 kW<br>(690 V) Three Phase, NO 3 kW                                     |
| Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ ) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 64 A  |
| Number of Auxiliary Contacts NC                             | 0  |
| Number of Auxiliary Contacts NO                             | 1  |
| Rated Operational Current AC-15 ( $I_e$ )                   | (24 V) 4 A<br>(120 V) 4 A<br>(500 V) 2 A<br>(220 / 240 V) 4 A<br>(380 / 400 V) 3 A   |
| Rated Operational Current DC-13 ( $I_e$ )                   | (24 V) 2.5 A<br>(110 V) 0.7 A<br>(220 / 240 V) 0.4 A   |
| Conventional Free-air Thermal Current ( $I_{th}$ )          | Main Circuit 12 A  |
| Rated Control Circuit Voltage ( $U_c$ )                     | 24 V AC  |
| Coil Operating Limits                                       | (acc. to IEC 60947-4-1) for AC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)  |
| Degree of Protection  | Auxiliary Circuit Terminals IP20   |

|  |  |
|--|--|
|  | Control Circuit Terminals IP20<br>Main Circuit Terminals IP20  |
| Mechanical Durability                  | 10000000 cycle   |
| Minimum Switching Capacity             | Auxiliary Circuit 17 V<br>Auxiliary Circuit 5 mA   |
| Maximum Electrical Switching Frequency | (AC-1) 300 cycles per hour<br>(AC-15) 600 cycles per hour<br>(AC-3) 600 cycles per hour<br>(DC-1) 600 cycles per hour<br>(DC-13) 600 cycles per hour<br>(DC-3) 600 cycles per hour |
| Mounting on DIN Rail                   | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715<br>TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715   |
| Power Loss                             | at Rated Operating Conditions per Pole 2 W<br>at Rated Operating Conditions AC-1 per Pole 1 W  |
| Standards                              | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1   |

## Technical UL/CSA

|                                  |  |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC  |
| Full Load Amps Motor Use         | (115 V AC) Single Phase 5.8 A<br>(200 V AC) Three Phase 4.8 A<br>(220 ... 240 V AC) Three Phase 6.8 A<br>(230 V AC) Single Phase 4.9 A<br>(440 ... 480 V AC) Three Phase 4.8 A<br>(550 ... 600 V AC) Three Phase 1.7 A |
| Horsepower Rating UL/CSA         | (115 V AC) Single Phase 0.25 Hp<br>(200 V AC) Three Phase 1 Hp<br>(220 ... 240 V AC) Three Phase 2 Hp<br>(230 V AC) Single Phase 0.5 Hp<br>(440 ... 480 V AC) Three Phase 3 Hp<br>(550 ... 600 V AC) Three Phase 1 Hp  |
| General Use Rating UL/CSA        | (300 V AC) 8 A   |
| Contact Rating UL/CSA            | A600   |

## Environmental

|  |  |
|--|--|
| Ambient Air Temperature                        | Operation -25 ... +55 °C<br>Storage -40 ... +80 °C                     |
| Maximum Operating Altitude Permissible         | 2000 m   |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 15g  |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 5 ... 150 Hz  |
| RoHS Status                                    | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |

## Certificates and Declarations

|                                 |                     |
|---------------------------------|---------------------|
| BV Certificate                  | 1SAA920000-0204     |
| CB Certificate                  | 1SAA938000-2002     |
| CQC Certificate                 | CQC2003010304064033 |
| cURus Certificate               | cUL_E191658         |
| Declaration of Conformity - CCC | 2020980304001854    |
| Declaration of Conformity       | 1SAD101100-3101     |

- CE

|                                     |                  |
|-------------------------------------|------------------|
| Declaration of Conformity<br>- UKCA | 1SAD201100-3101  |
| DNV GL Certificate                  | 1SAA938000-0306  |
| EAC Certificate                     | 1SAA920000-2702  |
| KC Certificate                      | 1SAA938000-1501  |
| LR Certificate                      | 1SAA938000-0504  |
| RMRS Certificate                    | 1SAA938000-0704  |
| UL Certificate                      | E191658-19880915 |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | 10 piece      |
| Package Level 1 Width             | 108 mm        |
| Package Level 1 Height            | 69 mm         |
| Package Level 1 Depth /<br>Length | 247 mm        |
| Package Level 1 Gross<br>Weight   | 1.775 kg      |
| Package Level 1 EAN               | 4013614412967 |

## Classifications

|                                       |   |
|---------------------------------------|---|
| Object Classification Code            | Q   |
| ETIM 4                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                                | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                                | EC000066 - Power contactor, AC switching  |
| ETIM 7                                | EC000066 - Power contactor, AC switching  |
| ETIM 8                                | EC000066 - Power contactor, AC switching  |
| eClass                                | V11.0 : 27371003                          |
| UNSPSC                                | 39121529                                  |
| IDEA Granular Category<br>Code (IGCC) | 4761 >> Magnet contactor, AC-switching    |

## Accessories

| Identifier      | Description                 | Type      | Quantity | Unit Of<br>Measure |
|-----------------|-----------------------------|-----------|----------|--------------------|
| GJL1201319R0003 | CA6-11M-P Auxiliary Contact | CA6-11M-P | 1        | piece              |
| GJL1201319R0004 | CA6-11N-P Auxiliary Contact | CA6-11N-P | 1        | piece              |
| GJL1201319R0002 | CA6-11E-P Auxiliary Contact | CA6-11E-P | 1        | piece              |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

