



## Power supply 50W DALI

- 50W Power supply with built-in PWM-dimmer
- Mono
- Controlled with DALI signal
- 1 Channel / 1 address
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

**Output:** Constant Voltage(CV)  
**Input voltage:** 100 - 240VAC  
**Output voltage:** 24VDC  
**Output power:** 50W  
**Output current:** 2,08A  
**DALI-address:** 1  
**IP-grade:** IP20  
**Operating temperature:** -20°C ~ +45°C  
**Dimensions:** L:210 W:50 H:32 mm

Art.no.	Product
S32007	Power supply 50W DALI

Wiring diagram page 80



## Power supply 100W DALI

- 100W Power supply with built-in PWM-dimmer
- Mono, RGB, RGBW og DW
- Controlled with DALI signal
- 4 Channels / 4 addresses
- Protection against overload, short circuit and overheating
- For 24V LED-strips (Mono, RGB, RGBW og DW) and other products with 24V operating voltage

**Output:** Constant Voltage(CV)  
**Input voltage:** 100 - 240VAC  
**Output voltage:** 4x24VDC  
**Output power:** 1x100W / 2x50W / 3x33W / 4x25W  
**Output current:** 1x4,2A / 2x2,1A / 3x1,4A / 4x1,05A  
**DALI-address:** 4  
**IP-grade:** IP20  
**Operating temperature:** -20°C ~ +45°C  
**Dimensions:** L:244 W:64 H:32 mm

Art.no.	Product
S32015	Power supply 100W DALI

Wiring diagram page 81



## RF to DALI DT6

- RF to DALI Group and Scene Controller
- Controlled by RF Wall Panel / Remote Control and converts the RF signal to DALI bus
- Programmed to 1 DALI group or as broadcast
- For single coloured light source
- Can be controlled with pulse signal

**Type:** DALI Gateway  
**Connection:** DALI bus, Push  
**Radio Frequency:** 869,5 MHz  
**Installation:** Recessed  
**Input voltage:** From DALI bus  
**System Consumption:** 8mA  
**Operating temperature:** 0° ~ +40°  
**Dimensions:** L:46 W:45 H:20,5 mm

Art.no.	Product
S21019	RF to DALI DT6

Wiring diagram page 84



## Wall panel DALI Mono

- DALI master for use without central DALI bus
- Can work both as master and slave
- Modes: Group, Address or Broadcast
- Fits in a standard wall box
- Remembers last light level
- 1 channel with up to 4 scenarios (S52034 only)

**Type:** DALI MCU  
**Connection:** DALI, L, N  
**Installation:** Recessed  
**Voltage:** 100-240VAC  
**System Consumption:** 15mA / 4mA (S52002)  
**DALI bus-Output power:** 100mA / 52mA (S52002)  
**Operating temperature:** 0° ~ +40°  
**Dimensions:** L:86 W:86 H:29 mm

Art.no.	Product
S52034	Mono Wall panel DALI MCU Touch

S52000 Dimmer wall DALI MCU

Wiring diagram page 86