

**SCHUKO socket outlet 16 A 250 V~ with shutter
Plug terminals**



Specification	Order No.	Packing unit	PS	EAN
 cream white glossy	4453 01	10/100	01	4010337093718
 Pure white glossy	4453 03	10/100	01	4010337093732
 Pure white matt	4453 27	10/100	01	4010337093763
 Anthracite	4453 28	10/100	11	4010337093770
 Colour aluminium	4453 26	10	11	4010337093756
 Black matt	4453 005	10/100	11	4010337093701
 Grey matt	4453 015	1/5	11	4010337093725
 Stainless steel	4453 600	1/5	11	4010337093787
 Bronze / black	4453 603	1/5	11	4010337093794



Bronze / cream white

4453 613

1/5

11

4010337093817

Features

- The support ring is earthed in connection with the mounting claws and claw screws.
- Quick mounting (approx. 3.5 turns per mounting claw).
- Expanding claws in the housing.
- Easier claw mounting thanks to robust PZ1 / slotted / PH screw head drive.
- Simplified installation thanks to patented arrangement of the large keyhole profiles using box screws.
- Low installation depth.
- Large, ergonomically shaped release levers.
- Sturdy earth bar with solid earthing fingers.
- Sturdy and corrosion-resistant steel support ring.
- Shatter-proof thermoplastic base.

Technical data

Installation depth:	29 mm
Conductors:	Rigid and flexible
Connection cross section - for conductors from:	1.5 mm ² to 2.5 mm ²
Ambient temperature - shutter:	0°C to +45°C

Notes

- Increased contact protection (Safety Plus) in accordance with IEC 60884-1.
-