

Dynamic White 14,4W — SLC Scandinavian P20 P54 P67 CV 24VDC O















• This LED-strip combines 2 types of diodes: 2400K and 6500K, which gives a dynamic white light spectre

• Changing light temperature from ulta warm 2400K to day-like 6500K will modify room's ambient

· Adjust light colour temperature as you desire with our user friendly stand-alone controls, which fit any installation

• Suitable in any solution, as direct, decorative and background light

• 120 LED diodes per meter give smooth and uniform linear light


• Shall be installed in aluminum profiles, to ensure sufficient cooling and long product lifetime

120 LED pr. meter Diodes: Every 12. diode (100 mm) **Cutting point:** 2 meter cable on each end Connection:

Max length: 5 meter 24 VDC Voltage:

3 MacAdam: 120° Beam angle:

-10°C ~ +45°C Operating temperature: 50 000 hours (L70B50) **Expected lifetime:**



Art.no.	Colour temp.	Lumen	Wattage	IP-grade	Length	Width	Height
S14007	2400K-6500K	1200 lm/m	14,4 W/m	IP20	5 m	10 mm	2 mm
S14008	2400K-6500K	1000 lm/m	14,4 W/m	IP54	5 m	10 mm	2,5 mm
S14009	2400K-6500K	1000 lm/m	14,4 W/m	IP67	5 m	12 mm	4 mm