



## Power supply RF 100W Mono, RGB, RGBW, DW

- 100W Power supply with built-in PWM-dimmer
- Mono, RGB, RGBW and DW
- Dimmable both with PushDim and different remote controls, making this a simple and practical power supply for multi-coloured lighting
- Protection against overload, short circuit and overheating
- For 24V LED-strips and other products with 24V operating voltage

**Output:** Constant Voltage(CV)  
**Input voltage:** 100 - 240VAC  
**Output voltage:** 4x24VDC  
**Output power:** 1x100W / 2x50W / 3x33W / 4x25W  
**Output current:** 1x4,2A / 2x2,1A / 3x1,4A / 4x1,05A  
**Radio Frequency:** 869,5 MHz  
**IP-grade:** IP20  
**Operating temperature:** -20°C ~ +45°C  
**Dimensions:** L:244 W:64 H:32 mm

| Art.no.       | Product                      |
|---------------|------------------------------|
| <b>S32003</b> | Power supply PushDim/RF 100W |

Wiring diagram page 80



DW

## Wall panel RF DW

- Ultra-sensitive glass panel with touch function
- Accurate and fast control at light level
- 4 different zones - separately or simultaneously
- Memory function with 2 scenarios, remembers last light level
- 2x256 different levels
- Backlighting
- Fits in a standard wall box


**Voltage:** 100-240VAC  
**Radio Frequency:** 869,5 MHz  
**Zones:** 4  
**Scenarios:** 2  
**Dimensions:** L:86 W:86 H:29 mm

| Art.no.       | Product                        |
|---------------|--------------------------------|
| <b>S50009</b> | Wall panel RF Touch 4 Zones DW |

DW

## Remote control RF DW

- Remote control for Dynamic White LED-strips
- Control of amount of light / colour with buttons
- Loop mode from warm to cold
- Control up to 4 Zones
- Save 1 scenario (colour/light amount level)
- Wall mount with magnet (included)
- For SLC RF-system



**Voltage:** CR2025-battery (included)  
**Radio Frequency:** 869,5 MHz  
**Zones:** 4  
**Scenarios:** 1  
**Dimensions:** L:136 W:39 H:11 mm

| Art.no.       | Product                    |
|---------------|----------------------------|
| <b>S50006</b> | Remote control RF DW black |



DW

## Wall panel RF Rotary

- 1 Zone Dynamic White
- On / Off by pressing the wheel
- Double tap to control colour / dimming
- Dimming/colour change by rotating the wheel
- Fits in a standard wall box
- Battery powered (battery included)
- Installation depth: 19.4 mm



Also available as table model:  
**Art.no.: S50007**  
[www.tlg.no](http://www.tlg.no)

**Voltage:** CR2032-battery (included)  
**Radio Frequency:** 869,5 MHz  
**Zones:** 1  
**Scenarios:** -  
**Dimensions:** L:86 W:86 H:42 mm

| Art.no.       | Product                    |
|---------------|----------------------------|
| <b>S50008</b> | Wall panel RF potmeter DW  |
| <b>S50007</b> | Remote control RF table DW |