



Color: ■ orange

Physical data	
Width	1 mm / 0.039 inches
Height	108 mm / 4.252 inches
Depth	42 mm / 1.654 inches

Mechanical data	
Mounting type	snap-on type

Material data	
Note (material data)	Information on material specifications can be found here
Color	orange
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.107 MJ
Weight	3.6 g

Environmental requirements	
Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4045454383053
Customs tariff number	85389099990



Environmental Product Compliance	
RoHS Compliance Status	Compliant, No Exemption

Approvals / Certificates

Declarations of conformity and manufacturer's declarations			Approvals for hazardous areas		
			PTB 0102 Ex ec IIC Gc  IECEx		
Approval	Standard	Certificate Name	Approval	Standard	Certificate Name
ATEX-Attestation of Conformity WAGO GmbH & Co. KG	-	-	ATEX KIWA Netherlands B.V.	-	KIWA 17ATEX0030 U
Railway WAGO GmbH & Co. KG	-	Railway Ready	CCC CNEX	GB/T 3836.3	2020312313000180 (Ex ec IIC Gc)
			IECEx KIWA Netherlands B.V.	-	IECEx KIWA 17.0014U (Ex ec IIC Gc)

Downloads

Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 2002-2992	

Documentation

Additional Information				Bid Text			
Technical Section	pdf	2240.62 KB		2002-2992	19.02.2019	xml	
				2002-2992	27.04.2017	doc	
						2.51 KB	
						23.50 KB	

CAD/CAE-Data

CAD data				CAE data			
2D/3D Models 2002-2992				EPLAN Data Portal 2002-2992			
							
				WSCAD Universe 2002-2992			
							
				ZUKEN Portal 2002-2992			
							