

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 500 V, nominal current: 17.5 A, number of connections: 4, connection method: Push-in connection, Rated cross section: 1.5 mm<sup>2</sup>, cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- In addition to the testing option in the double function shaft, all terminal blocks provide an additional test pick-off
- The compact design and front connection enable wiring in a confined space
- The Push-in connection terminal blocks are characterized by the system features of the CLIPLINE complete system and by easy and tool-free wiring of conductors with ferrules or solid conductors
- Tested for railway applications

## Commercial data

|                                      |                    |
|--------------------------------------|--------------------|
| Item number                          | 3208197            |
| Packing unit                         | 50 pc              |
| Minimum order quantity               | 50 pc              |
| Sales key                            | BE2213             |
| Product key                          | BE2213             |
| Catalog page                         | Page 39 (C-1-2019) |
| GTIN                                 | 4046356564328      |
| Weight per piece (including packing) | 5.146 g            |
| Weight per piece (excluding packing) | 4.828 g            |
| Customs tariff number                | 85369010           |
| Country of origin                    | DE                 |

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Technical data

### Notes

#### General

|      |                                                                                              |
|------|----------------------------------------------------------------------------------------------|
| Note | The max. load current must not be exceeded by the total current of all connected conductors. |
|------|----------------------------------------------------------------------------------------------|

### Product properties

|                       |                                |
|-----------------------|--------------------------------|
| Product type          | Multi-conductor terminal block |
| Product family        | PT                             |
| Area of application   | Railway industry               |
|                       | Machine building               |
|                       | Plant engineering              |
| Number of connections | 4                              |
| Number of rows        | 1                              |
| Potentials            | 1                              |

#### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 6 kV   |
| Maximum power dissipation for nominal condition | 0.56 W |

### Connection data

|                                                                   |                                                                                                          |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Number of connections per level                                   | 4                                                                                                        |
| Nominal cross section                                             | 1.5 mm <sup>2</sup>                                                                                      |
| Stripping length                                                  | 8 mm ... 10 mm                                                                                           |
| Internal cylindrical gage                                         | A1 / B1                                                                                                  |
| Connection in acc. with standard                                  | IEC 60947-7-1                                                                                            |
| Conductor cross section rigid                                     | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                             |
| Cross section AWG                                                 | 26 ... 16 (converted acc. to IEC)                                                                        |
| Conductor cross section flexible                                  | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                             |
| Conductor cross section, flexible [AWG]                           | 26 ... 16 (converted acc. to IEC)                                                                        |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>                                                             |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.14 mm <sup>2</sup> ... 1 mm <sup>2</sup>                                                               |
| Nominal current                                                   | 17.5 A                                                                                                   |
| Maximum load current                                              | 17.5 A (The maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal voltage                                                   | 500 V                                                                                                    |
| Nominal cross section                                             | 1.5 mm <sup>2</sup>                                                                                      |

Connection cross sections directly pluggable

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

|                                                                   |                                              |
|-------------------------------------------------------------------|----------------------------------------------|
| Conductor cross section rigid                                     | 0.25 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Conductor cross-section flexible (ferrule without plastic sleeve) | 0.34 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Flexible conductor cross section (ferrule with plastic sleeve)    | 0.34 mm <sup>2</sup> ... 1 mm <sup>2</sup>   |

## Ex data

### Rated data (ATEX/IECEx)

|                                                                          |                                       |
|--------------------------------------------------------------------------|---------------------------------------|
| Identification                                                           | Ex II 2 GD Ex eb IIC Gb               |
| Operating temperature range                                              | -60 °C ... 110 °C                     |
| Ex-certified accessories                                                 | 3208375 D-PT 1,5/S-QUATTRO            |
|                                                                          | 3030815 ATP-ST QUATTRO                |
|                                                                          | 1204504 SZF 0-0,4X2,5                 |
|                                                                          | 3022276 CLIPFIX 35-5                  |
|                                                                          | 3022218 CLIPFIX 35                    |
| List of bridges                                                          | Plug-in bridge / FBS 2-3,5 / 3213014  |
|                                                                          | Plug-in bridge / FBS 3-3,5 / 3213027  |
|                                                                          | Plug-in bridge / FBS 4-3,5 / 3213030  |
|                                                                          | Plug-in bridge / FBS 5-3,5 / 3213043  |
|                                                                          | Plug-in bridge / FBS 10-3,5 / 3213056 |
|                                                                          | Plug-in bridge / FBS 20-3,5 / 3213069 |
| Bridge data                                                              | 14.5 A / 1.5 mm <sup>2</sup>          |
| Ex temperature increase                                                  | 40 K (15 A / 1.5 mm <sup>2</sup> )    |
| Rated voltage                                                            | 352 V                                 |
| for bridging with bridge                                                 | 352 V                                 |
| - At bridging between non-adjacent terminal blocks                       | 220 V                                 |
| - At bridging between non-adjacent terminal blocks via PE terminal block | 220 V                                 |
| - At cut-to-length bridging                                              | 166 V                                 |
| - At cut-to-length bridging with cover                                   | 275 V                                 |
| - At cut-to-length bridging with partition plate                         | 352 V                                 |
| Rated insulation voltage                                                 | 320 V                                 |
| output                                                                   | (Permanent)                           |

### Ex level General

|                      |        |
|----------------------|--------|
| Rated current        | 15 A   |
| Maximum load current | 15 A   |
| Contact resistance   | 1.5 mΩ |

### Ex connection data General

|                              |                                              |
|------------------------------|----------------------------------------------|
| Nominal cross section        | 1.5 mm <sup>2</sup>                          |
| Rated cross section AWG      | 16                                           |
| Connection capacity rigid    | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Connection capacity AWG      | 26 ... 16                                    |
| Connection capacity flexible | 0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup> |
| Connection capacity AWG      | 26 ... 16                                    |

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 3.5 mm  |
| End cover width    | 2.2 mm  |
| Height             | 63.2 mm |
| Depth              | 30.5 mm |
| Depth on NS 35/7,5 | 32 mm   |
| Depth on NS 35/15  | 39.5 mm |

## Material specifications

|                                                                  |             |
|------------------------------------------------------------------|-------------|
| Color                                                            | gray        |
| Flammability rating according to UL 94                           | V0          |
| Insulating material group                                        | I           |
| Insulating material                                              | PA          |
| Static insulating material application in cold                   | -60 °C      |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24           | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26           | HL 1 - HL 3 |
| Surface flammability NFPA 130 (ASTM E 162)                       | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)          | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                           | passed      |

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 7.3 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                     |
|--------------------------------------------------|-------------------------------------|
| Requirement temperature-rise test                | Increase in temperature $\leq 45$ K |
| Result                                           | Test passed                         |
| Short-time withstand current 1.5 mm <sup>2</sup> | 0.18 kA                             |
| Result                                           | Test passed                         |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 1.89 kV     |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

## Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Result                  | Test passed |

## Test for conductor damage and slackening

|                                |                               |
|--------------------------------|-------------------------------|
| Rotation speed                 | 10 rpm                        |
| Revolutions                    | 135                           |
| Conductor cross section/weight | 0.14 mm <sup>2</sup> / 0.2 kg |
|                                | 1.5 mm <sup>2</sup> / 0.4 kg  |
| Result                         | Test passed                   |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                |
|------------------------|------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2022-06            |
| Spectrum               | Service life test category 2, bogie-mounted    |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level              | 11.83 (m/s <sup>2</sup> ) <sup>2</sup> /Hz     |
| Acceleration           | 4.25g                                          |
| Test duration per axis | 5 h                                            |
| Test directions        | X-, Y- and Z-axis                              |
| Result                 | Test passed                                    |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2022-06 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 30g                                 |
| Shock duration                 | 18 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|                                         |                                                                                                                              |
|-----------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)         | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport) | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60 °C to                                                           |

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

|                                          |                 |
|------------------------------------------|-----------------|
|                                          | +70°C)          |
| Ambient temperature (assembly)           | -5 °C ... 70 °C |
| Ambient temperature (actuation)          | -5 °C ... 70 °C |
| Permissible humidity (operation)         | 20 % ... 90 %   |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Drawings

Circuit diagram



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/gb/products/3208197>

**DNV**

Approval ID: TAE00003JE



**CSA**

Approval ID: 2030668

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 15 A                  | 26 - 14           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 300 V                 | 15 A                  | 26 - 14           | -                           |
| Use group D |                       |                       |                   |                             |
|             | 600 V                 | 5 A                   | 26 - 14           | -                           |



**IECEE CB Scheme**

Approval ID: DE1-62964

|  | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|--|-----------------------|-----------------------|-------------------|-----------------------------|
|  | 500 V                 | -                     | -                 | 0.14 - 1.5                  |



**cULus Recognized**

Approval ID: E60425

|             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|-------------|-----------------------|-----------------------|-------------------|-----------------------------|
| Use group B |                       |                       |                   |                             |
|             | 300 V                 | 15 A                  | 26 - 14           | -                           |
| Use group C |                       |                       |                   |                             |
|             | 300 V                 | 15 A                  | 26 - 14           | -                           |
| Use group D |                       |                       |                   |                             |
|             | 600 V                 | 5 A                   | 26 - 14           | -                           |



**LR**

Approval ID: LR2371832TA



**NK**

Approval ID: 14ME0912



**RS**

Approval ID: 22.44.01.00083.250

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>



**BV**  
Approval ID: 39980/B0 BV

|                                                                                   |                                                        |                       |                   |                             |
|-----------------------------------------------------------------------------------|--------------------------------------------------------|-----------------------|-------------------|-----------------------------|
|  | <b>VDE Zeichengenehmigung</b><br>Approval ID: 40039739 |                       |                   |                             |
|                                                                                   | Nominal voltage $U_N$                                  | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                                                                   | 500 V                                                  | 17.5 A                | -                 | 0.14 - 1.5                  |

**ABS**  
Approval ID: 21-2192245-PDA



**EAC Ex**  
Approval ID: RU C-DE.AB72.B.02351



**IECEx**  
Approval ID: IECEx SEV13.0005U



**ATEX**  
Approval ID: SEV13ATEX0159U



**CCC**  
Approval ID: 2020322313000631



**UKCA-EX**  
Approval ID: CML 22UKEX1224U



**IECEx**  
Approval ID: IECEx SEV13.0005U



**ATEX**  
Approval ID: SEV13ATEX0159U

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141120 |
| ECLASS-13.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Environmental product compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Accessories

**i** Note: Applying some accessories below might limit this product.

### FBS 2-3,5 - Plug-in bridge

3213014

<https://www.phoenixcontact.com/gb/products/3213014>



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: red

**i** Max. current carrying capacity: 17.5 A

### FBS 3-3,5 - Plug-in bridge

3213027

<https://www.phoenixcontact.com/gb/products/3213027>



Plug-in bridge, pitch: 3.5 mm, number of positions: 3, color: red

**i** Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 4-3,5 - Plug-in bridge

3213030

<https://www.phoenixcontact.com/gb/products/3213030>



Plug-in bridge, pitch: 3.5 mm, number of positions: 4, color: red

 Max. current carrying capacity: 17.5 A

---

## FBS 5-3,5 - Plug-in bridge

3213043

<https://www.phoenixcontact.com/gb/products/3213043>



Plug-in bridge, pitch: 3.5 mm, number of positions: 5, color: red

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 10-3,5 - Plug-in bridge

3213056

<https://www.phoenixcontact.com/gb/products/3213056>



Plug-in bridge, pitch: 3.5 mm, number of positions: 10, color: red

 Max. current carrying capacity: 17.5 A

---

## FBS 20-3,5 - Plug-in bridge

3213069

<https://www.phoenixcontact.com/gb/products/3213069>



Plug-in bridge, pitch: 3.5 mm, number of positions: 20, color: red

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 2-3,5 BU - Plug-in bridge

3213086

<https://www.phoenixcontact.com/gb/products/3213086>



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: blue

 Max. current carrying capacity: 17.5 A

---

## FBS 3-3,5 BU - Plug-in bridge

3213099

<https://www.phoenixcontact.com/gb/products/3213099>



Plug-in bridge, pitch: 3.5 mm, number of positions: 3, color: blue

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 4-3,5 BU - Plug-in bridge

3213109

<https://www.phoenixcontact.com/gb/products/3213109>



Plug-in bridge, pitch: 3.5 mm, number of positions: 4, color: blue

 Max. current carrying capacity: 17.5 A

---

## FBS 5-3,5 BU - Plug-in bridge

3213112

<https://www.phoenixcontact.com/gb/products/3213112>



Plug-in bridge, pitch: 3.5 mm, number of positions: 5, color: blue

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 10-3,5 BU - Plug-in bridge

3213125

<https://www.phoenixcontact.com/gb/products/3213125>



Plug-in bridge, pitch: 3.5 mm, number of positions: 10, color: blue

 Max. current carrying capacity: 17.5 A

---

## FBS 20-3,5 BU - Plug-in bridge

3213138

<https://www.phoenixcontact.com/gb/products/3213138>



Plug-in bridge, pitch: 3.5 mm, number of positions: 20, color: blue

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 2-3,5 GY - Plug-in bridge

3213153

<https://www.phoenixcontact.com/gb/products/3213153>



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: gray

 Max. current carrying capacity: 17.5 A

---

## FBS 3-3,5 GY - Plug-in bridge

3213167

<https://www.phoenixcontact.com/gb/products/3213167>



Plug-in bridge, pitch: 3.5 mm, number of positions: 3, color: gray

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 4-3,5 GY - Plug-in bridge

3213180

<https://www.phoenixcontact.com/gb/products/3213180>



Plug-in bridge, pitch: 3.5 mm, number of positions: 4, color: gray

 Max. current carrying capacity: 17.5 A

---

## FBS 5-3,5 GY - Plug-in bridge

3213183

<https://www.phoenixcontact.com/gb/products/3213183>



Plug-in bridge, pitch: 3.5 mm, number of positions: 5, color: gray

 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## FBS 10-3,5 GY - Plug-in bridge

3213196

<https://www.phoenixcontact.com/gb/products/3213196>

Plug-in bridge, pitch: 3.5 mm, number of positions: 10, color: gray



 Max. current carrying capacity: 17.5 A

---

## FBS 20-3,5 GY - Plug-in bridge

3213206

<https://www.phoenixcontact.com/gb/products/3213206>

Plug-in bridge, pitch: 3.5 mm, number of positions: 20, color: gray



 Max. current carrying capacity: 17.5 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## RB ST (2,5/4)-1,5/S - Reducing bridge

3214356

<https://www.phoenixcontact.com/gb/products/3214356>



Reducing bridge, pitch: 6.7 mm, number of positions: 2, length: 23 mm, color: red

 Max. current carrying capacity: 24 A

---

## RB ST 16-1,5/S - Reducing bridge

3213254

<https://www.phoenixcontact.com/gb/products/3213254>



Reducing bridge, pitch: 10 mm, number of positions: 2, length: 37 mm, color: red

 Max. current carrying capacity: 24 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## RB ST 10-1,5/S - Reducing bridge

3213252

<https://www.phoenixcontact.com/gb/products/3213252>



Reducing bridge, pitch: 3.5 mm, number of positions: 2, length: 36 mm, color: red

 Max. current carrying capacity: 24 A

---

## RB ST 6-1,5/S - Reducing bridge

3213250

<https://www.phoenixcontact.com/gb/products/3213250>



Reducing bridge, pitch: 8 mm, number of positions: 2, length: 30 mm, color: red

 Max. current carrying capacity: 24 A

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## GBS-ZB/26X6 - Group marker label for terminal marking

0809298

<https://www.phoenixcontact.com/gb/products/0809298>



Group marking label, snaps onto terminal center for screw, spring-cage and quick connection terminal blocks, labeled with ESL 26x6 mm or EST 25x6 mm, in the foot part with Zack marker strip, length: 29 mm

---

## ATP-ST QUATTRO - Partition plate

3030815

<https://www.phoenixcontact.com/gb/products/3030815>

Partition plate, depth: 45 mm, width: 2 mm, height: 90.9 mm, color: gray



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## D-PT 1,5/S-QUATTRO - End cover

3208375

<https://www.phoenixcontact.com/gb/products/3208375>

End cover, depth: 24.3 mm, width: 2.2 mm, height: 63.2 mm, color: gray



---

## D-PT 1,5/S-QUATTRO-0,8 OG - End cover

1029591

<https://www.phoenixcontact.com/gb/products/1029591>

End cover, depth: 24.3 mm, width: 0.8 mm, height: 63.2 mm, color: orange



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## Al-S 1 - 8 TQ - Ferrule

1200293

<https://www.phoenixcontact.com/gb/products/1200293>



Ferrule, S-Slimline, sleeve length: 8 mm, color: turquoise

---

## NS 35/ 7,5 PERF 2000MM - DIN rail perforated

0801733

<https://www.phoenixcontact.com/gb/products/0801733>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/ 7,5 UNPERF 2000MM - DIN rail, unperforated

0801681

<https://www.phoenixcontact.com/gb/products/0801681>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/ 7,5 WH PERF 2000MM - DIN rail perforated

1204119

<https://www.phoenixcontact.com/gb/products/1204119>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



## NS 35/ 7,5 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204122

<https://www.phoenixcontact.com/gb/products/1204122>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

---

## NS 35/ 7,5 AL UNPERF 2000MM - DIN rail, unperforated

0801704

<https://www.phoenixcontact.com/gb/products/0801704>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/ 7,5 ZN PERF 2000MM - DIN rail perforated

1206421

<https://www.phoenixcontact.com/gb/products/1206421>



DIN rail perforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/ 7,5 ZN UNPERF 2000MM - DIN rail, unperforated

1206434

<https://www.phoenixcontact.com/gb/products/1206434>



DIN rail, unperforated, Pack of 25 (50 m), acc. to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



## NS 35/ 7,5 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

0801762

<https://www.phoenixcontact.com/gb/products/0801762>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

---

## NS 35/ 7,5 CAP - End cap

1206560

<https://www.phoenixcontact.com/gb/products/1206560>

DIN rail end piece, for DIN rail NS 35/7.5



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/15 PERF 2000MM - DIN rail perforated

1201730

<https://www.phoenixcontact.com/gb/products/1201730>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

---

## NS 35/15 UNPERF 2000MM - DIN rail, unperforated

1201714

<https://www.phoenixcontact.com/gb/products/1201714>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/15 WH PERF 2000MM - DIN rail perforated

0806602

<https://www.phoenixcontact.com/gb/products/0806602>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: white

---

## NS 35/15 WH UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1204135

<https://www.phoenixcontact.com/gb/products/1204135>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Steel, Galvanized, white passivated, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/15 AL UNPERF 2000MM - DIN rail, unperforated

1201756

<https://www.phoenixcontact.com/gb/products/1201756>



DIN rail, unperforated, similar to EN 60715, material: Aluminum, uncoated, Standard profile, color: silver

---

## NS 35/15 ZN PERF 2000MM - DIN rail perforated

1206599

<https://www.phoenixcontact.com/gb/products/1206599>



DIN rail perforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## NS 35/15 ZN UNPERF 2000MM - DIN rail, unperforated

1206586

<https://www.phoenixcontact.com/gb/products/1206586>



DIN rail, unperforated, Pack of 25 (50 m), similar to EN 60715, material: Steel, galvanized, Standard profile, color: silver

---

## NS 35/15 CU UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201895

<https://www.phoenixcontact.com/gb/products/1201895>



DIN rail, unperforated, Pack of 10 (20 m), similar to EN 60715, material: Copper, uncoated, Standard profile, color: copper-colored

# PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



## NS 35/15 CAP - End cap

1206573

<https://www.phoenixcontact.com/gb/products/1206573>

DIN rail end piece, for DIN rail NS 35/15



---

## NS 35/15-2,3 UNPERF 2000MM-VPE 10 - DIN rail, unperforated

1201798

<https://www.phoenixcontact.com/gb/products/1201798>



DIN rail, unperforated, Pack of 10 (20 m), acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, Standard profile 2.3 mm, color: silver

## PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



### ZB 3,5:UNBEDRUCKT - Zack marker strip

0829414

<https://www.phoenixcontact.com/gb/products/0829414>



Zack marker strip, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 3.5 x 10.5 mm, Number of individual labels: 10

---

### ZB 3,5 CUS - Zack marker strip

0829415

<https://www.phoenixcontact.com/gb/products/0829415>



Zack marker strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 3.5 mm, lettering field size: 3.5 x 10.5 mm, Number of individual labels: 10

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## ZB 3,5,LGS:FORTL.ZAHLEN - Zack marker strip

0801404

<https://www.phoenixcontact.com/gb/products/0801404>




Zack marker strip, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 3.5 x 10.5 mm, Number of individual labels: 10

---

## ZB 3,5,QR:FORT.ZAHLEN - Zack marker strip

0801405

<https://www.phoenixcontact.com/gb/products/0801405>



Zack marker strip, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 3.5 x 10.5 mm, Number of individual labels: 10

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## UCT-TM 3,5 - Marker for terminal blocks

0829484

<https://www.phoenixcontact.com/gb/products/0829484>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 2.95 x 10.5 mm, Number of individual labels: 102

---

## UCT-TM 3,5 CUS - Marker for terminal blocks

0829581

<https://www.phoenixcontact.com/gb/products/0829581>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into tall marker groove, for terminal block width: 3.5 mm, lettering field size: 2.95 x 10.5 mm, Number of individual labels: 102

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## GBS 3,5-25X3,5 - Group marker label for terminal marking

0830290

<https://www.phoenixcontact.com/gb/products/0830290>



Group marking label, snaps into terminal center for push-in terminal blocks ...1.  
5/S,  
Lettering field 25 x 3.5 mm, pitch 3.5 mm, labeled with EML (24 x 3)R

---

## GBS 3,5-25X12 - Group marker label for terminal marking

0830292

<https://www.phoenixcontact.com/gb/products/0830292>



Group marking label, snaps into terminal center for push-in terminal blocks ...1.  
5/S,  
Lettering field 25 x 12 mm, pitch 3.5 mm, labeled with EML (25.4 x 12.7)R

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## MPS-MT - Test plug

0201744

<https://www.phoenixcontact.com/gb/products/0201744>



Test plug, with solder connection up to 1 mm<sup>2</sup> conductor cross section, number of positions: 1, color: gray

---

## MPS-IH WH - Insulating sleeve

0201663

<https://www.phoenixcontact.com/gb/products/0201663>

Insulating sleeve, color: white



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## MPS-IH RD - Insulating sleeve

0201676

<https://www.phoenixcontact.com/gb/products/0201676>

Insulating sleeve, color: red




---

## MPS-IH BU - Insulating sleeve

0201689

<https://www.phoenixcontact.com/gb/products/0201689>

Insulating sleeve, color: blue



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## MPS-IH YE - Insulating sleeve

0201692

<https://www.phoenixcontact.com/gb/products/0201692>

Insulating sleeve, color: yellow



---

## MPS-IH GN - Insulating sleeve

0201702

<https://www.phoenixcontact.com/gb/products/0201702>

Insulating sleeve, color: green



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## MPS-IH GY - Insulating sleeve

0201728

<https://www.phoenixcontact.com/gb/products/0201728>

Insulating sleeve, color: gray



---

## MPS-IH BK - Insulating sleeve

0201731

<https://www.phoenixcontact.com/gb/products/0201731>

Insulating sleeve, color: black



# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## TMT (EX9,5)R - Marker for terminal blocks

0828295

<https://www.phoenixcontact.com/gb/products/0828295>



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into tall marker groove, for terminal block width: 30000 mm, lettering field size: 9.5 x 50000 mm, Number of individual labels: 1

---

## US-TM 100 - Marker for terminal blocks

0829255

<https://www.phoenixcontact.com/gb/products/0829255>



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, lettering field size: 104 x 9.8 mm, Number of individual labels: 13

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## PS-3,5 - Test plug

3031010

<https://www.phoenixcontact.com/gb/products/3031010>



Test plug, Modular test plug, number of positions: 1, color: red

---

## DP PS-3,5 - Spacer plate

3031011

<https://www.phoenixcontact.com/gb/products/3031011>



Spacer plate, depth: 33.5 mm, width: 3.5 mm, height: 15.9 mm, number of positions: 1, color: red

## PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



## PS-3,5/E - Test plug

3031012

<https://www.phoenixcontact.com/gb/products/3031012>




Test plug, Individual test plug, number of positions: 1, color: red

---

## ZBF 3,5:UNBEDRUCKT - Zack Marker strip, flat

0829392

<https://www.phoenixcontact.com/gb/products/0829392>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 3.5 x 5.2 mm, Number of individual labels: 10

# PT 1,5/S-QUATTRO - Feed-through terminal block




3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## ZBF 3,5 CUS - Zack Marker strip, flat

0829394

<https://www.phoenixcontact.com/gb/products/0829394>



Zack Marker strip, flat, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 3.5 mm, lettering field size: 3.5 x 5.2 mm, Number of individual labels: 10

---

## ZBF 3,5,LGS:FORTL.ZAHLEN - Zack Marker strip, flat

0801406

<https://www.phoenixcontact.com/gb/products/0801406>



Zack Marker strip, flat, Strip, white, labeled, printed horizontally: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 5.15 x 3.5 mm, Number of individual labels: 10

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## ZBF 3,5,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0801407

<https://www.phoenixcontact.com/gb/products/0801407>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 5.15 x 3.5 mm, Number of individual labels: 10

---

## UCT-TMF 3,5 - Marker for terminal blocks

0829486

<https://www.phoenixcontact.com/gb/products/0829486>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 3.5 mm, lettering field size: 2.7 x 4.7 mm, Number of individual labels: 108

## PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



## UCT-TMF 3,5 CUS - Marker for terminal blocks

0829644

<https://www.phoenixcontact.com/gb/products/0829644>



Marker for terminal blocks, can be ordered: by sheet, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 3.5 mm, lettering field size: 2.7 x 4.7 mm, Number of individual labels: 108

---

## SZF 0-0,4X2,5 - Screwdriver

1204504

<https://www.phoenixcontact.com/gb/products/1204504>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

## PT 1,5/S-QUATTRO - Feed-through terminal block

3208197

<https://www.phoenixcontact.com/gb/products/3208197>



### ST-BW 0 - Actuation tool

1200135

<https://www.phoenixcontact.com/gb/products/1200135>

Actuation tool, for all 1.5 mm<sup>2</sup> spring cages from PT 1,5/S and FT 1,5/S



---

### PROJECT COMPLETE - Software

1050453

<https://www.phoenixcontact.com/gb/products/1050453>



Intuitive planning and marking software for configuring terminal strips and for professional marking of marking materials for terminal blocks, conductors, cables, devices, and systems. The software is available for download

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX CENTRUS 6S - Crimping pliers

1213144

<https://www.phoenixcontact.com/gb/products/1213144>



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm<sup>2</sup> ... 6 mm<sup>2</sup>, also for TWIN ferrules up to 2 x 4 mm<sup>2</sup>, automatic cross section adjustment, lateral insertion, equipped with fall protection

---

## CRIMPFOX CENTRUS 10S - Crimping pliers

1213154

<https://www.phoenixcontact.com/gb/products/1213154>



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm<sup>2</sup> ... 10 mm<sup>2</sup>, also for TWIN ferrules up to 2 x 4 mm<sup>2</sup>, automatic cross section adjustment, lateral insertion, equipped with fall protection

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX CENTRUS 6H - Crimping pliers

1213146

<https://www.phoenixcontact.com/gb/products/1213146>



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm<sup>2</sup> ... 6 mm<sup>2</sup>, also for TWIN ferrules up to 2 x 4 mm<sup>2</sup>, automatic cross section adjustment, lateral insertion, equipped with fall protection

---

## CRIMPFOX CENTRUS 10H - Crimping pliers

1213156

<https://www.phoenixcontact.com/gb/products/1213156>



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm<sup>2</sup> ... 10 mm<sup>2</sup>, also for TWIN ferrules up to 2 x 4 mm<sup>2</sup>, automatic cross section adjustment, lateral insertion, equipped with fall protection

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX 10S - Crimping pliers

1212045

<https://www.phoenixcontact.com/gb/products/1212045>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.14 mm<sup>2</sup> ... 10 mm<sup>2</sup>, unlockable pressure lock, lateral entry

---

## CRIMPFOX 6H - Crimping pliers

1212046

<https://www.phoenixcontact.com/gb/products/1212046>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.14 mm<sup>2</sup> ... 6 mm<sup>2</sup>, unlockable pressure lock, lateral entry

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX 2,5-M - Crimping pliers

1212719

<https://www.phoenixcontact.com/gb/products/1212719>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, lateral entry, trapezoidal crimp

---

## CRIMPFOX 6-M - Crimping pliers

1212720

<https://www.phoenixcontact.com/gb/products/1212720>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6.0 mm<sup>2</sup>, lateral entry, trapezoidal crimp

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX 6 - Crimping pliers

1212034

<https://www.phoenixcontact.com/gb/products/1212034>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6.0 mm<sup>2</sup>, lateral entry, trapezoidal crimp

---

## CRIMPFOX 6T - Crimping pliers

1212037

<https://www.phoenixcontact.com/gb/products/1212037>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6 mm<sup>2</sup>, lateral entry, trapezoidal crimp

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX 6T-F - Crimping pliers

1212038

<https://www.phoenixcontact.com/gb/products/1212038>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.25 mm<sup>2</sup> ... 6 mm<sup>2</sup>, front entry, trapezoidal crimp

---

## CRIMPFOX 6S-F - Crimping pliers

1212043

<https://www.phoenixcontact.com/gb/products/1212043>



Crimping pliers, for ferrules without insulating collar according to DIN 46228 Part 1 and ferrules with insulating collar according to DIN 46228 Part 4, 0.5 mm<sup>2</sup> ... 6 mm<sup>2</sup>, front entry, square crimp

# PT 1,5/S-QUATTRO - Feed-through terminal block



3208197

<https://www.phoenixcontact.com/gb/products/3208197>

## CRIMPFOX-M - Crimping pliers

1212072

<https://www.phoenixcontact.com/gb/products/1212072>

Basic pliers, for accommodating dies for a wide range of type of contacts



---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT Ltd

Halesfield 13, Telford

Shropshire, TF7 4PG

01952 681700

[info@phoenixcontact.co.uk](mailto:info@phoenixcontact.co.uk)