



Color: ■ gray

Physical data	
Width	3 mm / 0.118 inches
Height	17 mm / 0.669 inches
Depth	25 mm / 0.984 inches

Material data	
Note (material data)	Information on material specifications can be found here
Color	gray
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.027 MJ
Weight	0.9 g

Environmental requirements	
Processing temperature	-35 ... +85 °C
Continuous operating temperature	-60 ... +105 °C

Commercial data	
Product Group	9 (Std Chassis Mt Blocks)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	300 (50) pcs
Packaging type	Box
Country of origin	CH
GTIN	4017332271028
Customs tariff number	85389099990



Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 260-361	↓

Documentation			
Additional Information		Bid Text	
Technical Section	pdf 2240.62 KB	260-361	19.02.2019
	↓	xml	2.55 KB
		260-361	17.08.2017
		doc	23.00 KB
			↓

CAD/CAE-Data	
CAD data	CAE data
2D/3D Models 260-361	EPLAN Data Portal 260-361
↓	↓
	WSCAD Universe 260-361
	↓
	ZUKEN Portal 260-361
	↓

1 Compatible Products
1.1 Optional Accessories
1.1.1 Installation
1.1.1.1 Mounting accessories



Item No.: 209-123
Mounting foot with screw; can be screwed on terminal blocks with fixing flange; 6.4 mm wide; gray