




Color: ■ orange

| Physical data |                        |
|---------------|------------------------|
| Width         | 1.5 mm / 0.059 inches  |
| Height        | 122 mm / 4.803 inches  |
| Depth         | 71.7 mm / 2.823 inches |

| Material data               |                                                                          |
|-----------------------------|--------------------------------------------------------------------------|
| Note (material data)        | <a href="#">Information on material specifications can be found here</a> |
| Color                       | orange                                                                   |
| Material group              | I                                                                        |
| Insulation material         | Polyamide (PA66)                                                         |
| Flammability class per UL94 | V0                                                                       |
| Fire load                   | 0.283 MJ                                                                 |
| Weight                      | 9.6 g                                                                    |

| Environmental requirements       |                 |
|----------------------------------|-----------------|
| Processing temperature           | -35 ... +85 °C  |
| Continuous operating temperature | -60 ... +105 °C |

| Commercial data       |                                  |
|-----------------------|----------------------------------|
| Product Group         | 1 (Rail Mounted Terminal Blocks) |
| eCl@ss 10.0           | 27-14-11-33                      |
| eCl@ss 9.0            | 27-14-11-33                      |
| ETIM 8.0              | EC000886                         |
| ETIM 7.0              | EC000886                         |
| PU (SPU)              | 50 (10) pcs                      |
| Packaging type        | Box                              |
| Country of origin     | DE                               |
| GTIN                  | 4017332264907                    |
| Customs tariff number | 85389099990                      |



| Environmental Product Compliance |                        |
|----------------------------------|------------------------|
| RoHS Compliance Status           | Compliant,No Exemption |

| Downloads                                |                   |
|------------------------------------------|-------------------|
| Environmental Product Compliance         |                   |
| Compliance Search                        |                   |
| Environmental Product Compliance 282-387 | <a href="#">↓</a> |

| Documentation |            |     |          |                   |
|---------------|------------|-----|----------|-------------------|
| Bid Text      |            |     |          |                   |
| 282-387       | 19.02.2019 | xml | 2.65 KB  | <a href="#">↓</a> |
| 282-387       | 03.03.2017 | doc | 23.50 KB | <a href="#">↓</a> |

| CAD/CAE-Data         |                                             |
|----------------------|---------------------------------------------|
| CAD data             | CAE data                                    |
| 2D/3D Models 282-387 | EPLAN Data Portal 282-387 <a href="#">↓</a> |
|                      | WSCAD Universe 282-387 <a href="#">↓</a>    |
|                      | ZUKEN Portal 282-387 <a href="#">↓</a>      |

| Installation Notes |
|--------------------|
|                    |

A lock-out seal can be used on the disconnect link in notched "I" position.