

SAFETY DATA SHEET

Glidex Spray 20%

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Glidex Spray 20%

Product no.

2000000, 2050000

Unique formula identifier (UFI)

6000-E083-C00R-U52T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

▼ Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Unipak A/S

Marktoften 3C

8464 Galten

Denmark

+45 8626 1177

www.unipak.dk

E-mail

sales@unipak.dk

Revision

07/02/2024

SDS Version

2.0

Date of previous version

24/03/2022 (1.0)

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Precautionary statement(s)

▼ **General**

If medical advice is needed, have product container or label at hand. (P101)
 Keep out of reach of children. (P102)
 Read label before use. (P103)

▼ **Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Do not spray on an open flame or other ignition source. (P211)
 Do not pierce or burn, even after use. (P251)

Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

-

▼ **Hazardous substances**

None known.

▼ **Additional labelling**

UFI: 6000-E083-C00R-U52T

2.3. **Other hazards**

▼ **Additional warnings**

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive. This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. ▼ **Substances**

Not applicable. This product is a mixture.

3.2. ▼ **Mixtures**

Product/substance	Identifiers	% w/w	Classification	Note
butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: Index No.: 601-004-01-8	50-<75%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	10-<25%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 UK-REACH: Index No.: 601-004-01-8	1-<5%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

▼ **Other information**

-

SECTION 4: First aid measures

4.1. **Description of first aid measures**

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

▼ Eye contact

If in eyes: Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Remove contact lenses. Seek medical assistance and continue flushing during transport.

▼ Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. ▼ Most important symptoms and effects, both acute and delayed

None known.

4.3. ▼ Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. ▼ Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: None

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Minor spills are collected with a cloth. Shall be contained in suitable and tightly closed disposal containers.

6.4. ▼ Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

5 - 45°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane

Long term exposure limit (8 hours) (ppm): 600

Long term exposure limit (8 hours) (mg/m³): 1450

Short term exposure limit (15 minutes) (ppm): 750

Short term exposure limit (15 minutes) (mg/m³): 1810

Annotations:

Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

No data available.

▼ PNEC

No data available.

8.2. ▼ Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

▼ Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

▼ Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

▼ Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of inadequate ventilation	A	Class 2 (medium capacity)	Brown	EN14387



Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-

Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
In the likelihood of direct or incidental exposure.	Nitrile	0,3	120	EN374-2



Eye protection

Type	Standards
In the likelihood of direct or incidental exposure, use face protection.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

▼ Colour

Colourless

▼ Odour / Odour threshold

Characteristic

pH

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

Testing not relevant or not possible due to the nature of the product.

▼ Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

▼ Particle characteristics

Testing not relevant or not possible due to the nature of the product.

Phase changes

▼ Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

▼ Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

Boiling point (°C)

-161.5

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

- ▼ Flash point (°C)
Not applicable - product is an aerosol
- Flammability (°C)
The material is ignitable.
- ▼ Auto-ignition temperature (°C)
Testing not relevant or not possible due to nature of the product.
- ▼ Lower and upper explosion limit (% v/v)
5 - 15

Solubility

- Solubility in water
Testing not relevant or not possible due to the nature of the product.
- n-octanol/water coefficient (LogKow)
Testing not relevant or not possible due to the nature of the product.
- Solubility in fat (g/L)
Testing not relevant or not possible due to the nature of the product.

9.2. Other information

- ▼ Oxidizing properties
Testing not relevant or not possible due to the nature of the product.
- ▼ Other physical and chemical parameters
No data available.

SECTION 10: Stability and reactivity

- 10.1. ▼ Reactivity
No data available.
- 10.2. Chemical stability
The product is stable under the conditions, noted in section 7 "Handling and storage".
- 10.3. ▼ Possibility of hazardous reactions
None known.
- 10.4. Conditions to avoid
Avoid static electricity.
Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.
- 10.5. Incompatible materials
Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.
- 10.6. Hazardous decomposition products
The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼ Acute toxicity

Product/substance	butane
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	1237 mg/l 2h.

Product/substance	propane
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	1237 mg/l air 2h.

Product/substance	isobutane
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50

Result: 1237 mg/l 2h. ·

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

▼ Long term effects

None known.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

▼ Other information

None known.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance	butane
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	7,71 mg/L ·

Product/substance	propane
Species:	Fish
Duration:	96 hours
Test:	LC50
Result:	27,98 mg/l ·

Product/substance	propane
Species:	Algae
Duration:	96 hours
Test:	EC50
Result:	7,71 mg/l ·

Product/substance	propane
Species:	Daphnia
Duration:	48 hours
Test:	LC50
Result:	46,6 mg/l ·

Product/substance	isobutane
Species:	Fish

Duration: 96 hours
 Test: LC50
 Result: 49,9 mg/l ·

Product/substance isobutane
 Species: Algae
 Duration: 96 hours
 Test: EC50
 Result: 19,37 mg/l ·

12.2. ▼ Persistence and degradability

Product/substance butane
 Conclusion: -
 Test: OECD 307 S 1110 - Aerobic and Anaerobic Transformation Soil

Product/substance propane
 Conclusion: -
 Test: OECD 307 S 1110 - Aerobic and Anaerobic Transformation Soil

12.3. ▼ Bioaccumulative potential

Product/substance butane
 LogKow: 1.0900
 Conclusion: Potential for bioaccumulation

Product/substance propane
 LogKow: 1,0900
 Conclusion: Potential for bioaccumulation

Product/substance isobutane
 LogKow: 1,0900
 Conclusion: Potential for bioaccumulation

12.4. Mobility in soil

butane
 LogKoc = 0.941571, High mobility potential.

12.5. ▼ Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. ▼ Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. ▼ Other adverse effects

This product contains substances with the potential of bioaccumulation resulting in the risk of accumulation in the food chain. Bioaccumulative substances are concentrated in adipose tissue and are not easily secreted.

SECTION 13: Disposal considerations

▼ Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)
 HP 3 - Flammable
 Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances

▼ Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

▼ Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: None

14.6. ▼ Special precautions for user

Not applicable.

14.7. ▼ Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

▼ Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

▼ UK-REACH, Annex XVII

butane is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

propane is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

isobutane is subject to UK-REACH restrictions, UK-REACH annex XVII (entry 40).

▼ Additional information

Not applicable.

▼ Sources

- The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).
- Control of Major Accident Hazards (COMAH) Regulations 2015.
- Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.
- Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.
- Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

- H220, Extremely flammable gas.
- H280, Contains gas under pressure; may explode if heated.

▼ Abbreviations and acronyms

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- CAS = Chemical Abstracts Service
- CE = Conformité Européenne (European conformity)
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- CSA = Chemical Safety Assessment
- CSR = Chemical Safety Report
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EINECS = European Inventory of Existing Commercial chemical Substances
- ES = Exposure Scenario
- EUH statement = CLP-specific Hazard statement
- EuPCS = European Product Categorisation System
- EWC = European Waste Catalogue
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IARC = International Agency for Research on Cancer (IARC)
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- OECD = Organisation for Economic Co-operation and Development
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SCL = A specific concentration limit
- SVHC = Substances of Very High Concern
- STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
- STOT-SE = Specific Target Organ Toxicity - Single Exposure
- TWA = Time weighted average
- UN = United Nations
- UVBC = Unknown or variable composition, complex reaction products or of biological materials
- VOC = Volatile Organic Compound
- vPvB = Very Persistent and Very Bioaccumulative

▼ Additional information

The classification of the mixture in regard to physical hazards has been based on experimental data.

▼ The safety data sheet is validated by

THA

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue

triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en