

416BS6W

Wall mounted inlet

2CMA167078R1000



Surface Inlet, earthing sleeve position 6h, rated current 16A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red

GENERAL

Product Name	Wall mounted inlet
Product ID	2CMA167078R1000
Function	Surface inlet
EAN	73926966784
Catalog Description	Surface inlet, 6h, 16A, IP67, 3P+N+E
Country of Origin	Czech Republic (CZ)
E-Number Finland	2421515
E-Number Norway	1542723
E-Number Sweden	E2417230
Standards	IEC 60309-1, -2
RoHS Status	Following EU Directive 2011/65/EU

TECHNICAL

Product Main Type	TBS
Color	Red
Number of Poles	5
Clock Position	6Hour
Rated Current	16 ampere
Rated Voltage	200/346 ... 240/415 volt
Frequency	50 hertz 60 hertz
Degree of Protection	IP67 IP69
Cable Cross-Section	1.5...4 mm ²
Housing Material	Thermoplastic (PBT)
Plug Angle	Angled
Product Group	Tough&Safe

DIMENSIONS

Product Net Width	99 millimetre
Product Net Height	134 millimetre
Product Net Length	211 millimetre
Product Net Depth	211 millimetre
Product Net Weight	0.43 kilogram

PACKAGING

Package Width	152 millimetre
Package Height	265 millimetre
Package Gross Weight	0.43 kilogram
Package Length	120 millimetre
Package Units	box 1 piece