

### 48503061

# Active-energy meter COUNTIS E12 Direct 80A dual tariff + MID



Strong points

- RS485 (MODBUS) communication, M-Bus, Ethernet or pulse outputs

- Multi-tariff
- B+D module MID-certified

#### General characteristics

- Compact dimensions.
- Measurement accuracy: 1%.
- Displayed on backlit screen.
- Multi-measurement available on display.

#### Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62052-11
- EN 50470-1
- EN 50470-3

#### Access to resources (ex: manuals)

The COUNTIS E1x is a modular energy meter displaying the energy (kWh, kVArh and kVA) and other measurements directly on its backlit LCD display. It is designed for single-phase load metering and is used for direct connections of up to 80 A.

41113708

EC001506

#### Classification

UNSPSC

ETIM Class

L I IIVI Olass	L0001300
IGCC	6341
Commerce	
Effective date	2019-04-01
Country of origin	IT
ETIM - Electrical characteristics	
Nominal current (In) [A]	80
Max. current (Imax) [A]	80
Nominal voltage (Un) N-L [V]	184276
Nominal voltage (Un) L-L [V]	320480
Frequency [Hz]	5060
Accuracy class	В
Pole type	Single phase
Energy type	Effective power and blind power
Suitable for	Purchase/supply
Tariff type	Two-tariff
Tariff control	External
Measurement type load profile	No
Calibrated	Yes
Pulse output	Electrical
Pulse type	S0
Pulse rate [Imp/kWh (kvarh)]	1010
ETIM - Mechanical characteristics	
Escapement mechanism	No
Mounting method	DRA (DIN-rail adapter)
Width in number of modular spacings	2
With lock code	No
Degree of protection (IP)	IP51
ETIM - Technical features	
Type of meter	Electronic
Model	Direct measurement
Approval	Measuring Instruments Directive
Type of indication	Digital
Type of interface	None
EEC40 signature	No
Logistics	
GTIN/EAN	3596033073571
Customs number	9028301100

PC

0.24

0.05

0.105

2024-09-18 18:52:36

Price unit

Weight of the packing unit

Length of the packing unit

Width of the packing unit



## **COUNTIS E12 1PH 80A 2T MID**

Depth of the packing unit	0.09
Norms	
Conformity to standards	IEC
Technical Characteristics	
Application	Metering
Model	E12
Туре	1PH up to 80A, MID, double-tariff

2024-09-18 18:52:36