

48290578

## Sensor TF-600 1600-6000A



TF flexible current sensors measure the load currents of an electrical circuit and send the data to meters and Power Monitoring Devices or current modules via an RJ12 plug-and-play connection. Thanks to a wide measurement range, TF current sensors cover a wide current range from 100 to 6000 A, with only 7 references. TF flexible current sensors can be used with DIRIS Digiware I modules, DIRIS A-40 and DIRIS B.

### Strong points

- Plug & Play
- Accuracy as per standard IEC 61557-12
- Safe locking mechanism
- Installation
- Simplified installation

### General characteristics

- Range from 150 to 6000A.
- Used with DIRIS Digiware, DIRIS A-40 and DIRIS B.

### Compliance with standards

- IEC 61557-12
- ISO 14025
- UL

### Access to resources (ex: manuals)

### Classification

UNSPSC	83101808
ETIM Class	EC002048
IGCC	6042

### Commerce

Effective date	2017-12-01
Country of origin	IT

### ETIM - Electrical characteristics

Rated primary current [A]	6000
Rated secondary current [A]	0.1
Rated secondary apparent power [VA]	0.1
Accuracy class	0.2S
Overcurrent limiting factor	FS 10
Calibrated	Yes

### ETIM - Mechanical characteristics

With contact protection	Yes
Height opening [mm]	600..600
Width opening [mm]	600..600
Opening diameter [mm]	600
Snap mounting	Yes
With copper rail	Yes
Secondary connection	Plug-in connection

### ETIM - Technical features

Model	Attachable current transformer
Number of primary inputs	1

### Logistics

GTIN/EAN	3596033018732
Customs number	8504312990
Price unit	PC
Weight of the packing unit	0.291
Length of the packing unit	0.04
Width of the packing unit	0.24
Depth of the packing unit	0.28

### Norms

Conformity to standards	IEC UL
-------------------------	------------

### Technical Characteristics

Model	TF
Opening	600
Rated current	6000
Secondary rated current	RJ12