




Ø:275

SLC White 660/695/735 lm 2700/3200/4000K Ra>80 Not dimmable IP65

Outdoor luminaire for wall. Easy installation. Has through wiring for both concealed and open installation. Robust luminaire with IK10 and IP65.

Electrical

Input	220-240V 50/60Hz
Rated power	7 W
Control type	Not dimmable
MAX. qty on 16A Circuit Breaker (Type C)	175
Expected lifetime (25°C)	100 000 hours
Light reduction (25°C)	L90B50
Expected lifetime at max Ta	50.000
Light reduction at max Ta	L90B50
Operating temperature (Ta)	-20°C ~ +45°C
Insulation class	Class II

Light technic

Lumen	660/695/735 lm
Efficacy	110 lm/W
Colour temperature	2700/3200/4000K
Colour rendering (CRI/Ra)	Ra>80
MacAdam (SDCM)	3
Beam angle fixed	110 °
Optics	Opal

Mechanical

Installation	Veggmontering, Utenpåliggende tak/vegg, Utenpåliggende vegg, Wall mounting, Surface-mounted roof/wall, Surface-mounted wall
Material, main	Plastic
Material, optics	Polycarbonate
IP class	IP65
IK grade	IK10
Color	White
RAL	RAL9016
UV resistant	Yes
Suitable for	Indoor / Outdoor

Dimensions

Height	59 mm
Diameter	275 mm