



LIMBO SOFT

220-240V 50/60 Hz 350mA LED 10W IP44*

34 mm

Ø95 mm

Cut out: Ø82-84 mm

EN: Included dimmable LED driver.
NO: Inkludert dimmbar LED driver.
SE: Inklusive dimbar LED driver.

EN: Cable connection.
NO: Ledningstilkobling.
SE: Kabelanslutning.

Max. 16A
Max. 2,5mm²

EN: CORRESPONDING PRODUCT.
NO: TILHØRENDE PRODUKT.
SE: TILLHÖRANDE PRODUKT.

NO EL. NR:	SE E. NR:	DIMMER:
32 249 20	74 657 18	DL BOX LOW
32 249 21	74 657 19	DL BOX HIGH

BRAND: UNILAMP/LUZENSE

NO EL. NR:	SE E. NR:	DIMMER:
14 059 01	13 602 79	KDT-500E 1 POLE
14 059 02	13 602 80	KDT-500E 2 POLE
14 059 03	13 602 40	UNIVERSAL KDT-500IE

BRAND: UNILAMP/LUZENSE

NO EL. NR:	SE E. NR:	DIMMER:
66 146 18	79 809 01	DALI DIMMABLE LED DRIVER 10W 350MA

BRAND: UNILAMP/LUZENSE

EN: May be covered by insulation sheet.
NO: Kan overdekkes av isolasjonsmatter.
SE: Kan övertäckas av isolationsmattor.

* EN: IP44 from the luminaire underside.
NO: IP44 fra armaturens underside.
SE: IP44 från armaturens undersida.

0 m

EN: Minimum distance to flammable material in the beam direction.
NO: Minimumsavstand til brennbart materiale i armaturens stråleretning.
SE: Minsta avstånd mellan brännbart material och lampans ljusrättning.